Recent Progress from the DEAP-3600 Dark Matter Direct Detection Experiment

Jocelyn Monroe,
Royal Holloway University of London &
High Energy Accelerator Research Organization (KEK)

12th Patras Workshop on Axions, WIMPs, and WISPs

Jeju Island, South Korea
June 22, 2016

DEAP Collaboration: 65 researchers in Canada, UK, and Mexico



Outline

Experiment Strategy

The DEAP-3600 Detector

Recent Progress, Commissioning and Calibration

The Low-Background Frontier: Status and Prospects



P. Gondolo, Patras'16

so far: <1 event at ~1E-45 cm^2, therefore need ***at least***
1E-47 cm^2 sensitivity for 100 events to measure M_X,σ

Single Phase Liquid Nobles, a la Neutrinos

high light yield from 4π PMT coverage, self-shielding of liquid target, only detect scintillation



XMASS: 832 kg LXe detector at Kamioka, running from 2013, future 5T detector for dark matter and neutrino physics

DEAP/CLEAN: LAr at SNOLAB. DEAP 3.6T, MiniCLEAN 0.5T commissioning now, DEAP physics start Summer 2015, project <0.6 background/3000 kg-days, 1E-46 cm^2 sensitivity



no electric fields = scale to large mass (O(100 T))
1) no pile-up from ms-scale electron drift in TPC
2) no recombination in E field
but background discrimination from scintillation only!

Why Argon

price, ease of purification, and LAr scintillates
~40 photons/keV with fast and slow components





Table 3: Scintillation parameters for liquid neon, argon, and xenon.

Parameter	Ne	Ar	Xe
Yield ($\times 10^4$ photons/MeV)	1.5	4.0	4.2
prompt time constant τ_1 (ns)	2.2	6	2.2
late time constant τ_3	15 μs	1.59 μs	21 ns
I_1/I_3 for electrons	0.12	0.3	0.3
I_1/I_3 for nuclear recoils	0.56	3	1.6
λ(peak) (nm)	77	128	174
Rayleigh scattering length (cm)	60	90	30

Lippincott et al., Phys.Rev.C 78: 035801 (2008)



identify, reject electronic backgrounds via pulse shape vs. time difference

McKinsey & Coakley, Astropart. Phys. 22, 355 (2005).
Boulay and Hime, Astropart. Phys. 25, 179 (2006)

- ★ Critically important for LAr: Ar-39 background beta decay at 1 Bq/kg, with 550 keV endpoint.
- ★ Very large detectors possible, with e^- ID for neutrino-electron scattering backgrounds

Argon Detectors



DEAP (SNOLAB), DarkSide (LNGS), ArDM (Canfranc) operating

'ppb-ppt' pulse shape discrimination (PSD) to identify e^- vs. Ar recoils.

leakage probability of e^- into nuclear recoil F_{prompt} region leverages x250 difference in scintillation time constants in argon.

*Fancier statistics gain ~10x in PSD leakage
Akashi-Ronquest et al., Astropart. Phys. 65 (2014) 40

DEAP-3600: measures PSD to 3E-8 in DEAP-1, predict >1E-10 in DEAP-3600 *(arXiv:0904.2930)*

DarkSide-50: measure depletion x1600, in 50kg detector, zero background limit *(arXiv:1510.00702)*

ARGO: Coordination of LAr detectors, ArDM will test depleted UAr samples with 100x sensitivity.





Outline

Experiment Strategy

The DEAP-3600 Detector

Recent Progress, Commissioning and Calibration

DEAP-3600 Detector



85 cm radius acrylic sphere contains 3600 kg of liquid argon (LAr)

★ TPB coats inside surface of sphere, to wavelength shift from 128 nm to 420 nm

★ viewed by 255 8″ Hamamatsu R5912 HQE PMTs (32% QE, 75% coverage)

★ 50 cm of acrylic light guide between LAr and PMTs to mitigate PMT neutrons

★ PTFE filler blocks between light guides to moderate neutrons

Outer steel shell prevents LAr / water mixing (important for safety!)

Inside 8.5m diameter water tank, with 48 8″ R1408 PMTs for muon veto, and to moderate cavern neutrons and gammas.

6200′ underground in SNOLAB Cube Hall

Background Strategy





Electrons and Gammas:

- Ar-39 decay rate ~1 Bq/kg, Q=550 keV. Dominates data rate.
- mitigated with pulse shape discrimination (PSD)
- threshold for PSD determines energy threshold for dark matter search

Alphas and Radon Progeny:

- stringent radiopurity control, ex-situ assays
- resurfacing of vessel before TPB + argon fill
- fiducialization, determines fiducial volume for dark matter search

Neutrons and Gammas:

- passive moderation
- cross-check with active tagging: measure neutron inelastic scattering gammas
- stringent radiopurity control for (alpha,n)

Background (in Fid Vol)	DEAP-3600 Goal
Radon in Ar	< 1.4 nBq/kg
Surface α's	< 100 μBq/m^2
Neutrons (all sources)	< 2 pBq/kg
Ar-39	< 2 pBq/kg
Total (3 tonne-yr)	**< 0.6 events**

Electron/Gamma Mitigation in DEAP-3600

Background target corresponds to <0.2 events in 3 Tonne-years.

This requires 1E-10 leakage of electrons into WIMP region.

Projected leakage in DEAP-3600 is <1E-10, based on fitting DEAP-1 data over 60-260 PE + noise model from measurements of DEAP-3600 electronics.





Main increase in PSD from light yield: 8 PE/keVee.

Effect of systematics in PE counting is important!

Developed Bayesian PE counter for DEAP-3600, with full PMT after pulsing model+correction, and measured TPB time constants ex-situ, vs. T.

Akashi-Ronquest, et al.,Astropart. Phys. 65 (2014) 40
Veloce, et al., JINST 11 (2016) no.06, P06003

Radon Mitigation in DEAP-3600

Dangerous Radon (Rn) backgrounds come from decay of Rn progeny on surfaces, and between Acrylic Vessel (AV) and wavelength shifter (TPB).

Dominant source of Rn comes from plate-out on AV and acrylic during manufacture and construction.

So, sand off a thin layer of of acrylic from inside of the detector before TPB deposition, x25 reduction.



With a

gigantic

robot!

Radon Mitigation in DEAP-3600

Dangerous Radon (Rn) backgrounds come from decay of Rn progeny on surfaces, and between Acrylic Vessel (AV) and wavelength shifter (TPB).

Dominant source of Rn comes from plate-out on AV and acrylic during manufacture and construction.

So, sand off a thin layer of of acrylic from inside of the detector before TPB deposition, x25 reduction.



With a

gigantic

robot!



double click to start

Resurfacing and TPB Deposition

Removed 0.4 mm from acrylic vessel inner surface.

Based on material assay and exposure history of the acrylic vessel, the projected residue activity after resurfacing is ~10 alphas/m^2/day.

Deposited 3 um of TPB in two runs (total 200 hours).

TPB thickness chosen to optimize light level vs. background from Po-210 decays.







Measured residue activity in 1 month vacuum run (1/16) prior to cool down for LAr fill.

Neutron Mitigation in DEAP-3600

Dominant source of neutron backgrounds comes from (alpha,n) in PMT glass.

Passive: shield LAr target from PMTs by 50 cm of acrylic to moderate this neutron flux.

Active: tag inelastic neutron scatters by characteristic gammas.

(A. Butcher, PhD thesis 2015)

Validate both active and passive mitigation efficiency using external tagged AmBe source.



(In 3 years)	# of neutrons (produced)	Events in ROI
Acrylic vessel	<44 (Ge γ-assay)	<0.096
Light guides	<127 (Ge γ-assay)	<0.015
Filler blocks	<173 (Ge γ-assay)	<0.034
PMTs	2.6x10	0.140
PMT mounts	7565	0. 010
Rn emanation	<44	<0.081
Rn deposition (3 months	38	0.010
Other sources		0.04
Total	**<2.7x10**	**<0.35**







Outline

Experiment Strategy

The DEAP-3600 Detector

Recent Progress, Commissioning and Calibration

DEAP-3600 Construction

DEAP-3600 Construction



DEAP-3600 Construction



DEAP-3600 Calibration Systems

0. Optical Calibration Systems:
- in-situ array of reflectors, fed by LEDs via fibers, fixed in position in 20 light guides + 2 at neck
- movable, multi-wavelength laser-diffuser flask





1. Radioactive Source Calibrations:
- tagged Na-22 source Cal A,B,E pipes, Cal F racetrack
- tagged AmBe source in vertical pipes
- hot Th-232 source at neck, in vertical pipes
- Ar-39 in-situ



Data taking since 2/15



In-Situ PMT Commissioning

Acrylic Array of Reflectors fed by LEDs + Fibers:

- PMT gain matching
- low- and high-occupancy calibrations
- PMT afterpulsing measurement
- detector stability monitoring
- trigger performance validation
- tuning simulation optical model









installed AARF reflector + fiber sources



PMT Charge Calibration

PMT charge calibration model fits calibration data and dark rate data well for low+high occupancy.











Gain uniformity better than 10% before PMT voltage adjustment for fine gain matching.

In-Situ Optics Commissioning

Multi-wavelength laser-fed diffuser flask deployed through glovebox into detector

- z = +55,0,-55 cm
- phi = 0,90,180,270
- wavelength = 375, 405, 455 nm
- measure PMT + light guide relative efficiencies, PMT timing offsets
- extract TPB uniformity for optical model







multi-wavelength laser source

in-situ laser calibration campaigns in gas-filled detector in July, Aug. 2015

PMT Time Calibration

PMT signal digitization at 250 MHz. Raw signal has up to 32 ns offset from trigger, cable lengths, board-to-board timing, etc.

Electronics pulse pattern generator (PPG) signal injection for channel-to-channel timing correction:







laserball timing calibration used to measure timing offsets for each channel and correct.

Resulting PMT peak time spread: ~1 ns RMS

Water Veto

Before water fill, event rate in detector PMTs dominated by Cherenkov from gammas
- after water fill, rate drops as expected

Expected muon rate ~1.6/day
- measure high energy event rate of ~1/day

example high energy event:







Trigger Commissioning

Physics trigger on analog sum of charges on groups of PMTs (ASUM) to make decision.

Data compression (ZLE) happens on-board the waveform digitizers.







demonstrated stable operation at 2 kHz trigger rate ~ few PE threshold for detector.

AARF data used to verify PMT calibration with full vs. ZLE waveforms, and estimate trigger threshold in PE.

Liquid Argon Filling

Expect rate of Ar-39 beta decays dominates
- select Ar-39 events in the trigger, on a fast proxy for prompt fraction (Q_{narrow}/Q_{wide})

Rate consistent with expectation from load cell monitors and Ar-39 abundance (1 Bq/kg)







Ar-39 calibration underway for energy scale, position reconstruction

Summary & Outlook

DEAP3600 will be the 1st demonstration of single-phase liquid Argon technology.

- discovery reach of 10^{-46} cm^2 in 3 T-yrs exposure,
- LAr filling now…. *Stay tuned!*



- prototype for kT-scale, O(10s) keV threshold detector for 'low-energy frontier' physics



<u>Neutrino lesson</u>: key to kT-scale, low-rate sensitive detectors is simple, open-volume design.

Other Slides

Alpha Scintillation in TPB

TPB wavelength-shifts from 128 nm to visible (fluorescence)
ex-situ test benches for spectrum, efficiency, angular dist.
V. M. Gehman et al., NIM A 654 1 (2011) 116-121

Alpha scintillation in TPB has rejection power,
ex-situ test stand finds 11±5 and 275±10 ns
fast and slow time constants, and fast:total
intensity ratio of 0.67±0.03
(cf. 7 ns and 1600 ns, and 0.75)
T. Pollmann et al., NIM A 635 1 (2011) 127-130









Calibration R&D Ex-Situ

What if we see 5 events? How would we know if its a signal?

- ex-situ measurement input to calibration analysis,
  (i) reduce systematics on energy, radius reconstruction,
  (ii) break correlations between parameters for MC tuning

  -measure angular distribution of TPB emission
  -measure TPB scattering length
  -measure the Rayleigh scattering length in LAr
  (new calculation: *Grace et al, arXiv:1502.04213*)
  -measure the scintillation time constant temperature dependence