

Doubling the Frascati INFN Beam Test Facility (BTF)

Bruno Buonomo¹, Luca Foggetta¹, <u>Claudio Di Giulio¹</u>, Paolo Valente²



1 INFN Laboratori Nazionali di Frascati 2 INFN Sezione di Roma







BTF in the DA Φ NE

The BTF (Beam Test Facility) is part of the DA ϕ NE accelerator complex: it is composed of a transfer line driven by a pulsed magnet allowing the diversion of electrons or positrons













TITAN Beta (Ca,USA) 1995

- S band LINear Accelerator ~60 m long
- Termoionic gun, 4x45 MW klystrons SLED 15 waveguide $2/3\pi$ SLAC type section 3m long.





Upgrade pulse width: ~ 150 ns







BTF

INFN

How the BTF works:

The primary beam collide $\approx 2x_0$, Cu produce a secondary beam







The Beam-Test Facility

- The users in BTF are able to know in real time the beam parameter (type of particle, energy, intensity, dimension and position).
- They have the accelerator complex services available for their setup: power supply, network, gas, DAQ, Vacuum staff, cryogenic.
- Usually BTF works in parasitic way respect to DAΦNE collider.

Demonstra	Para	sitic	Dedicated		
Parametri	With Cu target	Without Cu target	With Cu target	Without Cu target	
Particle	e⁺ or e⁻ (User)	e⁺ or e⁻ (Dafne status)	e ⁺ o (Use	re- er)	
Energy (MeV)	25–500	25–500 510		250–730 (e⁻) 250–530 (e⁺)	
Energy Resolution	1% at 500 MeV	0.5%	0.5%		
Repetition rate (Hz)	Variable from 10 to 49 1–49 (DAFNE status) (User)				
Pulse lenght (ns)	10 1.5–40 (150) (User)				
Intensity (particle/bunch)	1–10 ⁵ (Energy dependence)	10 ⁷ –1.5 10 ¹⁰	1–10 ⁵ Energy dependence	10 ³ -3 10 ¹⁰	
Max # of partic.	3.125 10 ¹⁰ part./s				
Beam size(mm)	0.5–25 (y) × 0.6–55 (x)				
Divergence (mrad)	1–1.5				







BTF products:

- Electron o positron:
 - Single particle
 - High Intensity
- "Tagged" photon
- Neutrons











BTF: Low Intensity

Single particle

- Primary beam attenuated by a Copper target
- Energy od Secondary from 500 up to 30MeV
- The multiplicity follow the Poisson distribution and user can select the mean value.
- Positron and electrons independent form the primary beam.
 Best beam







Secondary beam

2cm² MEDIPIX

6th Beam Telescopes and Test Beam Workshop Zürich 16 – 19 Jan-2018

POT Axis

ŝ

104

156

(07/03/2016):

440x420 μ m²





Diagnostics and services

- Diagnostic:
 - ICT
 - Medipix/Fitpix
 - Hodoscope
 - Silicon Tracker
 - Photon tag
 - Neutron detectors
 - Flags
 - Cams
 - GEM
 - Calorimeters

- Services:
 - 4 gas line
 - Water, air, HV, network.



- Remote controlled table(step up to 100 μ m, weight up to 200 Kg)
- LNF mechanical support
- DAFNE operator support
- DAFNE technician support







Why doubling the BTF:

We open 2 calls every year for experiments and tests beam and we need to reject about 50% of the requested beam time.

For the next years we want provide an hall for experiments that require irradiation test or long beam time, as for example the PADME experiment for the dark sector research.

And the new experimental hall where low intensity (up to 10⁶ e⁻) test beam on R&D detector beam time will be available.



- X Average of 200 beam days/year, 25-30 experimental groups, 150-200 users
- X Undergoing a major upgrade in 2018:
 - X Split beam-line for serving two experimental areas
 - **X** Shielding of second hall
 - **X** LINAC consolidation
 - X New control room







CDR in 2016



The BTF staff and upgrade team

INFN

Paolo Valente - Roma

Bruno Buonomo, Claudio Di Giulio, Luca Foggetta, David Alesini,

Maurizio Belli, Simone Bini, Bruno Bolli, Sergio Cantarella, Riccardo Ceccareli, Alberto Cecchinelli, Oreste Cerafogli, Renato Clementi, Enrico Di Pasquale, Alessandro Drago, Adolfo Esposito, Oscar Frasciello, Andrea Ghigo, Simona Incremona, Franco Iungo, Stefano Lauciani, Valerio Lollo, Roberto Mascio, Stefano Martelli, Luigi Pellegrino, Graziano Piermarini, Luis Antonio Rossi, Lucia Sabbatini, Claudio Sanelli, Franco Sardone, Giancarlo Sensolini, Serena Strabioli, Ruggero Ricci, Ugo Rotundo, Alessandro Stecchi, Angelo Stella, Raffaele Zarlenga – LNF







BTF

INFN

BTF doubling simulations



6th Beam Telescopes and Test Beam Workshop Zürich 16 – 19 Jan-2018



11



BTF doubling simulations

MADX



BTFZ ONFN 6th Beam To Zürich 16 –







BTF

INFŃ

BTF doubling simulations

MADX







BTF doubling simulations

Radio Protection Dossier:

- End of 2017: FISMEL Service start to request authorizations to National Institution and Government authority based on the engineering shielding final project.
- Additional diagnostic requested for neutrons and gamma monitoring.
- New search procedure and safety check implemented in the dossier.

Limit for free access area: 0.1 μ Sv/h, <10⁶/s













BTF-2 final layout

- Modified (and removable) staircase to get larger access space from the front of new hall
- Preserve DA PNE racks in order to have no interference with SIDDHARTA-2 run
- ③ Enlarged (top) side access for better use of the area and at the same time improve protection of racks area
- Additional labyrinth in place of sliding shielded door on the (bottom) side of new hall for simpler and faster civil engineering
- **5** Correctors added for **better beam control**

ÍNFŃ

6 Secondary vacuum for new BTF lines, separated from LINAC primary vacuum for safer operation: added pump, modify interlock.







Final layout: 3D







New area









BTF

INFN

Civil engineering and shielding (1/5)











Radio-protection paper-work on-going

Zürich 16 – 19 Jan-2018

Civil engineering and shielding (2/5)



Trave Tipo A1 L=335cm 1 pezzo 9 pezzi Trave Tipo A2 L=335cm 9 pezzi Trave Tipo B2 L=535 cm 1 pezzo Trave Tipo B1 L=535cm 8 pezzi

- New magnet power supplies: three racks in room upstairs of the (old) control room, path for cables identified without major intervention
- Path for additional cooling piping and power cables in preparation
- Cooling and power plants modifications in preparation
- Final project done, tender assigned
- Road consolidation & first demolitions starting in Dec. 2017









Present situation



New layout





6th Beam Telescopes and Test Beam Workshop Zürich 16 – 19 Jan-2018



20



Civil engineering and shielding (4/5)









Civil engineering and shieldings (5/5)









New magnets









Magnetic design

Main constraints

- Fit inside the existing BTF hall for turning by 135° and thus use the former control room as second experimental area
- Split the bending into three dipoles in order to control the dispersion

7ürich 16 – 19 Jan-2018

- Take into account a possible energy upgrade of the LINAC up to 1 GeV: at least 920 MeV secondary beams
 - As a consequence, iron core dipoles working close to saturation





Pulsed dipole



Beam energy (MeV)1000Curvature radius (m)21Gap (mm)21Pole width (mm)111Nominal flux density (T)1,1.Bending angle (deg)11N per pole (turns)31Ampere-turns/pole11055Yoke Width (mm)277Yoke Height (mm)355Yoke Length (mm)355Yoke Length (mm)365Overall Length (mm)355Overall Length (mm)355Overall Length (mm)355Overall Length (mm)355Overall Length (mm)911Good Field Region (mm)±22Field quality (ΔB/B)6,4E-03Integrated Field quality (ΔIB/IB)2,3E-03Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7x7 ΦNominal Current (A)310Nominal Resistive Voltage (V)111Rot (Ω)0,077Nominal Inductance (H)0,022Nominal Power (kVA)336Proposed Cable cross section (mm²)99Proposed Output PS Current (A)336Proposed Output PS Voltage (V)136Proposed Output PS Nortent (A)336Proposed Output PS Nortent (A)336Proposed Output PS Power (kVA)42,5WATER COOLING337Number of pancakes per pole337	Beam energy (MeV) Image: Curvature radius (m) Gap (mm) Image: Curvature radius (m) Pole width (mm) Image: Curvature radius (T) Bending angle (deg) Image: Curvature radius (T) Bending angle (deg) Image: Curvature radius (T) Bending angle (deg) Image: Curvature radius (T) Mper pole (turns) Image: Curvature radius (T) Ampere-turns/pole Image: Curvature radius (T) Yoke Width (mm) Image: Curvature radius (T) Yoke Height (mm) Image: Curvature radius (T) Yoke Length (mm) Image: Curvature radius (T) Overall Length (mm) Image: Curvature radius (T) Overall Length (mm) Image: Curvature radius (T) Good Field Region (mm) Image: Curvature radius (I) Field quality (\Delta B) Image: Curvature radius (\Delta B) Total weight (kg) Image: Curvature radius (I) Image: Curvature radius (I) Image: Curvature radius (I) Nominal Current (A) Image: Curvature radius (I) Nominal Inductance (H) Image: Curvature radius (I) Nominal Power (kVA) Image: Curvature radius (I) Maximum Line Cable lenght (m) Image: Curvature radius (I)	1000 3 25 110 1,11 5 36 11052 277 359 760 329 359 913
Curvature radius (m)21Gap (mm)21Pole width (mm)111Nominal flux density (T)1,1.Bending angle (deg)11N per pole (turns)31Ampere-turns/pole1105:Yoke Width (mm)27'Yoke Height (mm)355Yoke Length (mm)355Yoke Length (mm)322Overall Length (mm)355Overall Length (mm)911Good Field Region (mm)±22Field quality (ΔB/B)6,4E-03Integrated Field quality (ΔIB/IB)2,3E-03Total weight (kg)511ELECTRICAL INTERFACE511Conductor dimension7x7 Φ-Nominal Current (A)311Nominal Resistive Voltage (V)111Rot (Ω)0,072Nominal Inductance (H)0,022Nominal Power (kVA)336Proposed Cutput PS Current (A)336Proposed Output PS Current (A)336Proposed Output PS Voltage (V)136Proposed Output PS Now (kVA)42,5WATER COOLING347Number of pancakes per pole51	Curvature radius (m) Gap (mm) Gap (mm) Pole width (mm) Nominal flux density (T) Bending angle (deg) Bending angle (deg) N N per pole (turns) Ampere-turns/pole Yoke Width (mm) Yoke Height (mm) Yoke Length (mm) Yoke Length (mm) Overall Length (mm) Overall Height (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Rtot (Ω) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Proposed cable cross section (mm²)	3 25 110 1,11 5 36 11052 277 359 760 329 359 913
Gap (mm)2!Pole width (mm)111Nominal flux density (T)1,1;Bending angle (deg)11N per pole (turns)31Ampere-turns/pole1105;Yoke Width (mm)27Yoke Height (mm)35;Yoke Length (mm)35;Yoke Length (mm)32;Overall Length (mm)32;Overall Length (mm)35;Overall Length (mm)35;Overall Length (mm)32;Overall Length (mm)91;Good Field Region (mm)±2;Field quality (ΔB/B)6,4E-0;Integrated Field quality (ΔIB/IB)2,3E-0;Total weight (kg)51;Conductor dimension7x7 ΦNominal Current (A)31;Nominal Current (A)31;Nominal Inductance (H)0,02;Nominal Inductance (H)0,02;Nominal Power (kVA)33;Maximum Line Cable length (m)20;Proposed Cutput PS Current (A)33;Proposed Output PS Voltage (V)13;Proposed Output PS Norter (A)33;Proposed Output PS Norter (A)42;WATER COOLING14;Number of pancakes per pole5;	Gap (mm) Pole width (mm) Pole width (mm) Mominal flux density (T) Bending angle (deg) N N per pole (turns) Mampere-turns/pole Yoke Width (mm) Yoke Height (mm) Yoke Length (mm) Yoke Length (mm) Overall Length (mm) Overall Length (mm) Overall Height (mm) Mampere-turns/pole Overall Length (mm) Mampere-turns/pole Good Field Region (mm) Mampere-turns/pole Field quality (\DeltaB) Mampere-turns/pole Total weight (kg) Mampere-turns/pole Conductor dimension Mampere-turns/pole Nominal Current (A) Mampere-turns/pole Nominal inductance (H) Mammu Line Cable lenght (m) Nominal Power (kVA) Maximum Line Cable lenght (m)	25 110 1,11 5 36 11052 277 359 760 329 359 913
Pole width (mm)111Nominal flux density (T)1,1;Bending angle (deg)1N per pole (turns)3Ampere-turns/pole1105;Yoke Width (mm)27Yoke Height (mm)35;Yoke Length (mm)35;Yoke Length (mm)32;Overall Length (mm)32;Overall Length (mm)35;Overall Length (mm)32;Overall Length (mm)31;Good Field Region (mm)±2;Field quality (ΔB/B)6,4E-0;Integrated Field quality (ΔIB/IB)2,3E-0;Total weight (kg)51;Conductor dimension7x7 ΦNominal Current (A)31;Nominal Resistive Voltage (V)11;Rtot (Ω)0,07;Nominal Inductance (H)0,02;Nominal Power (kVA)33;Maximum Line Cable lenght (m)20;Proposed Cable cross section (mm²)9;Proposed Output PS Current (A)33;Proposed Output PS Voltage (V)13;Proposed Output PS Power (kVA)42;WATER COOLING51;Number of pancakes per pole5;	Pole width (mm) Image: Pole width (mm) Nominal flux density (T) Image: Pole (deg) Bending angle (deg) Image: Pole (turns) Ampere-turns/pole Image: Pole (turns) Ampere-turns/pole Image: Pole (turns) Yoke Width (mm) Image: Pole (turns) Yoke Width (mm) Image: Pole (turns) Yoke Height (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Good Field Region (mm) Image: Pole (turns) Field quality (ΔB/B) Image: Pole (turns) Integrated Field quality (ΔIB/IB) Image: Pole (turns) Total weight (kg) Image: Pole (turns) Dominal Current (A) Image: Pole (turns) Nominal Resistive Voltage (V) Image: Pole (turns) Rtot (Ω) Image: Pole (turns) Nominal Inductance (H) Image: Pole (turns) Nominal Power (kVA) Image: Pole (turns) Proposed cable cross section (mm²) Image: Pole (turns)	110 1,11 15 36 11052 277 359 760 329 359 913
Nominal flux density (T)1,1;Bending angle (deg)1N per pole (turns)3Ampere-turns/pole1105;Yoke Width (mm)27Yoke Height (mm)35;Yoke Length (mm)32;Overall Length (mm)32;Overall Height (mm)32;Overall Length (mm)32;Overall Length (mm)91;Good Field Region (mm) $\pm 2;$ Field quality ($\Delta B/B$)6,4E-0;Integrated Field quality ($\Delta IB/IB$)2,3E-0;Total weight (kg)51;ELECTRICAL INTERFACEConductor dimension7x7 ΦNominal Current (A)31;Nominal inductance (H)0,02;Nominal Inductance (H)0,02;Nominal Power (kVA)32;Maximum Line Cable lenght (m)20;Proposed Output PS Current (A)33;Proposed Output PS Voltage (V)11;Proposed Output PS Norrey (kVA)42;WATER COOLING33;Number of pancakes per pole5;	Nominal flux density (T) Image: Section (Market	1,11 15 36 11052 277 359 760 329 359 913
Bending angle (deg)1N per pole (turns)34Ampere-turns/pole1105;Yoke Width (mm)27Yoke Height (mm)35;Yoke Length (mm)35;Overall Length (mm)32;Overall Height (mm)32;Overall Height (mm)91;Good Field Region (mm)±2;Field quality (ΔB/B)6,4E-0;Integrated Field quality (ΔIB/IB)2,3E-0;Total weight (kg)51;ELECTRICAL INTERFACEConductor dimension7x7 ΦNominal Current (A)31;Nominal Resistive Voltage (V)11;Rtot (Ω)0,07;Nominal Inductance (H)0,02;Nominal Power (kVA)3;Maximum Line Cable lenght (m)20;Proposed Output PS Current (A)33;Proposed Output PS Voltage (V)11;Proposed Output PS Noltage (V)13;Proposed Output PS Power (kVA)42;WATER COOLING33;Number of pancakes per pole;	Bending angle (deg) Image: Pole (turns) Ampere-turns/pole Image: Pole (turns) Yoke Width (mm) Image: Pole (turns) Yoke Width (mm) Image: Pole (turns) Yoke Height (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Overall Length (mm) Image: Pole (turns) Good Field Region (mm) Image: Pole (turns) Field quality (\Delta B) Image: Pole (turns) Total weight (kg) Image: Pole (turns) Conductor dimension Image: Pole (turns) Nominal Current (A) Image: Pole (turns) Nominal Resistive Voltage (V) Image: Pole (turns) Rtot (Ω) Image: Pole (turns) Nominal Inductance (H) Image: Pole (turns) Nominal Power (kVA) Image: Pole (turns) Proposed cable cross section (mm²) Image: Pole (turns)	15 36 11052 277 359 760 329 359 913
N per pole (turns)34Ampere-turns/pole1105:Yoke Width (mm)27Yoke Height (mm)35:Yoke Length (mm)76:Overall Length (mm)32:Overall Length (mm)32:Overall Length (mm)91:Good Field Region (mm)±2:Field quality (ΔB/B)6,4E-0:Integrated Field quality (ΔIB/IB)2,3E-0:Total weight (kg)51:ELECTRICAL INTERFACEConductor dimension7x7 Φ-Nominal Current (A)31:Nominal Resistive Voltage (V)11:Rtot (Ω)0,07:Nominal Inductance (H)0,02!Nominal Power (kVA)33:Maximum Line Cable lenght (m)20Proposed Output PS Current (A)33:Proposed Output PS Voltage (V)13:Proposed Output PS Power (kVA)42;WATER COOLING33:Number of pancakes per pole5:	N per pole (turns) Ampere-turns/pole Ampere-turns/pole Yoke Width (mm) Yoke Width (mm) Yoke Length (mm) Yoke Length (mm) Overall Length (mm) Overall Length (mm) Overall Length (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Mominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	36 11052 277 359 760 329 359 913
Ampere-turns/pole1105:Yoke Width (mm)27Yoke Height (mm)35:Yoke Length (mm)76:Overall Length (mm)32:Overall Length (mm)35:Overall Length (mm)91:Good Field Region (mm)±2!Field quality (ΔB/B)6,4E-0:Integrated Field quality (ΔIB/IB)2,3E-0:Total weight (kg)51:ELECTRICAL INTERFACEConductor dimension7x7 Φ-Nominal Current (A)31:Nominal Resistive Voltage (V)11:Rtot (Ω)0,07:Nominal Inductance (H)0,02!Nominal Power (kVA)33:Maximum Line Cable lenght (m)20Proposed Output PS Current (A)33:Proposed Output PS Voltage (V)13:Proposed Output PS Noltage (V)13:Proposed Output PS Power (kVA)42;WATER COOLING142;Number of pancakes per pole5:	Ampere-turns/pole Yoke Width (mm) Yoke Height (mm) Yoke Length (mm) Overall Length (mm) Overall Length (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal Inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	11052 277 359 760 329 359 913
Yoke Width (mm)27Yoke Height (mm)35Yoke Length (mm)76Overall Length (mm)32Overall Length (mm)35Overall Length (mm)91Good Field Region (mm) ± 21 Field quality ($\Delta B/B$) $6,4E-03$ Integrated Field quality ($\Delta IB/IB$) $2,3E-03$ Total weight (kg)510ELECTRICAL INTERFACEConductor dimension $7x7 \Phi^2$ Nominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω) $0,073$ Nominal Inductance (H) $0,023$ Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Output PS Current (A)334Proposed Output PS Voltage (V)1134Proposed Output PS Noltage (V)134Proposed Output PS Power (kVA)425WATER COOLING34Number of pancakes per pole35	Yoke Width (mm) Image: Section (mm) Yoke Length (mm) Image: Section (mm) Overall Length (mm) Image: Section (mm) Overall Length (mm) Image: Section (mm) Good Field Region (mm) Image: Section (mm) Field quality (ΔB/B) Image: Section (MB/IB) Integrated Field quality (ΔIB/IB) Image: Section (MB/IB) Total weight (kg) Image: Section (MB/IB) Conductor dimension Image: Section (MB/IB) Nominal Current (A) Image: Section (MB/IB) Nominal Inductance (H) Image: Section (MB/IB) Nominal Power (kVA) Image: Section (MB/IB)	277 359 760 329 359 913
Yoke Height (mm)35Yoke Length (mm)76Overall Length (mm)322Overall Length (mm)355Overall Length (mm)911Good Field Region (mm) ± 22 Field quality ($\Delta B/B$)6,4E-03Integrated Field quality ($\Delta IB/IB$)2,3E-03Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7x7 Φ-Nominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,073Nominal Inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Output PS Current (A)334Proposed Output PS Voltage (V)1134Proposed Output PS Voltage (V)344Proposed Output PS Power (kVA)422,9WATER COOLING34Number of pancakes per pole35	Yoke Height (mm) Yoke Length (mm) Overall Length (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	359 760 329 359 913
Yoke Length (mm)760Overall Length (mm)322Overall Length (mm)355Overall Length (mm)911Good Field Region (mm)±21Field quality (ΔB/B)6,4E-00Integrated Field quality (ΔIB/IB)2,3E-01Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7x7 Φ-Nominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,075Nominal inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Output PS Current (A)334Proposed Output PS Voltage (V)1136Proposed Output PS Voltage (V)34Proposed Output PS Power (kVA)422,9WATER COOLING34Number of pancakes per pole35	Yoke Length (mm) Overall Length (mm) Overall Length (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	760 329 359 913
Overall Length (mm)32!Overall Height (mm)35!Overall Length (mm)91!Good Field Region (mm)±2!Field quality (ΔB/B)6,4E-0.0Integrated Field quality (ΔIB/IB)2,3E-0.0Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7x7 Φ-Nominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,075Nominal Inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Output PS Current (A)336Proposed Output PS Voltage (V)1136Proposed Output PS Power (kVA)42.5WATER COOLING337Number of pancakes per pole337	Overall Length (mm) Overall Height (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal Inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	329 359 913
Overall Height (mm)359Overall Length (mm)911Good Field Region (mm)±21Field quality (ΔB/B)6,4E-00Integrated Field quality (ΔIB/IB)2,3E-00Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7x7 ΦNominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,075Nominal inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Cutput PS Current (A)336Proposed Output PS Voltage (V)1136Proposed Output PS Power (kVA)422,5WATER COOLING	Overall Height (mm) Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal Inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	359 913
Overall Length (mm)91: Good Field Region (mm)91: 42!Good Field Region (mm)±2!Field quality (ΔB/B)6,4E-0.0Integrated Field quality (ΔIB/IB)2,3E-0.0Total weight (kg)511ELECTRICAL INTERFACEConductor dimension7X7 ΦNominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,073Nominal inductance (H)0,029Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Cutput PS Current (A)330Proposed Output PS Voltage (V)133Proposed Output PS Voltage (V)330Proposed Output PS Power (kVA)422,9WATER COOLING330Number of pancakes per pole330	Overall Length (mm) Good Field Region (mm) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Find Common	913
Good Field Region (mm)±2!Field quality (ΔB/B)6,4E-0.Integrated Field quality (ΔIB/IB)2,3E-0.Total weight (kg)511ELECTRICAL INTERFACEConductor dimension7X7 ΦNominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,075Nominal inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed Cable cross section (mm²)99Proposed Output PS Current (A)336Proposed Output PS Voltage (V)1136Proposed Output PS Power (kVA)425WATER COOLING337Number of pancakes per pole337	Good Field Region (mm) Field quality (ΔB/B) Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Final Amount and the section (mm²)	
Field quality (ΔB/B)6,4E-0.Integrated Field quality (ΔIB/IB)2,3E-0.Total weight (kg)510ELECTRICAL INTERFACEConductor dimension7X7 ΦNominal Current (A)310Nominal Resistive Voltage (V)111Rtot (Ω)0,073Nominal inductance (H)0,025Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed cable cross section (mm²)99Proposed Output PS Current (A)336Proposed Output PS Voltage (V)1136Proposed Output PS Power (kVA)422,5WATER COOLING337Number of pancakes per pole337	Field quality (ΔB/B) Integrated Field quality (ΔIB/IB) Total weight (kg) Integrated Field quality (ΔIB/IB) Total weight (kg) Integrated Field quality (ΔIB/IB) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Integrated Field quality (MIS)	±25
Integrated Field quality (ΔΙΒ/ΙΒ) 2,3E-0; Total weight (kg) 510 ELECTRICAL INTERFACE Conductor dimension 7x7 Φ Nominal Current (A) 310 Nominal Resistive Voltage (V) 111 Rtot (Ω) 0,073 Nominal inductance (H) 0,029 Nominal Power (kVA) 33 Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 99 Proposed Output PS Current (A) 336 Proposed Output PS Voltage (V) 133 Proposed Output PS Voltage (V) 133 Proposed Output PS Power (kVA) 42,9 WATER COOLING 336 Number of pancakes per pole 337	Integrated Field quality (ΔΙΒ/ΙΒ) Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	6,4E-03
Total weight (kg)511ELECTRICAL INTERFACEConductor dimension7x7 ΦNominal Current (A)311Nominal Resistive Voltage (V)111Rtot (Ω)0,074Nominal inductance (H)0,024Nominal Power (kVA)33Maximum Line Cable lenght (m)20Proposed cable cross section (mm²)99Proposed Output PS Current (A)336Proposed Output PS Voltage (V)136Proposed Output PS Power (kVA)422,9WATER COOLINGNumber of pancakes per pole35	Total weight (kg) ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Proposed cable cross section (mm²)	2,3E-03
ELECTRICAL INTERFACE Conductor dimension 7x7 Φ Nominal Current (A) 311 Nominal Resistive Voltage (V) 111 Rtot (Ω) 0,074 Nominal inductance (H) 0,029 Nominal Power (kVA) 319 Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 99 Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 1136 Proposed Output PS Power (kVA) 42,9 WATER COOLING 330 Number of pancakes per pole 330	ELECTRICAL INTERFACE Conductor dimension Nominal Current (A) Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Proposed cable cross section (mm²)	516
Conductor dimension7x7 ΦNominal Current (A)311Nominal Resistive Voltage (V)111Rtot (Ω)0,074Nominal inductance (H)0,029Nominal Power (kVA)31Maximum Line Cable lenght (m)24Proposed cable cross section (mm²)99Proposed Output PS Current (A)336Proposed Output PS Voltage (V)136Proposed Output PS Power (kVA)42,9WATER COOLING337Number of pancakes per pole337	Conductor dimension Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Proposed cable cross section (mm²)	
Nominal Current (A) 311 Nominal Resistive Voltage (V) 111 Rtot (Ω) 0,07 Nominal inductance (H) 0,02 Nominal Power (kVA) 31 Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 99 Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,9 WATER COOLING 330	Nominal Current (A) Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	7x7 Φ4
Nominal Resistive Voltage (V) 111 Rtot (Ω) 0,07 Nominal inductance (H) 0,02 Nominal Power (kVA) 31 Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 99 Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,5 WATER COOLING Number of pancakes per pole	Nominal Resistive Voltage (V) Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	316
Rtot (Ω) 0,07 Nominal inductance (H) 0,02 Nominal Power (kVA) 33 Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 99 Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,5 WATER COOLING Number of pancakes per pole	Rtot (Ω) Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²) Proposed cable cross section (mm²)	113
Nominal inductance (H) 0,02! Nominal Power (kVA) 3! Maximum Line Cable lenght (m) 20 Proposed cable cross section (mm²) 9! Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,5 WATER COOLING Number of pancakes per pole	Nominal inductance (H) Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm²)	0,078
Nominal Power (kVA) 3! Maximum Line Cable lenght (m) 2i Proposed cable cross section (mm²) 9! Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,5 WATER COOLING Number of pancakes per pole	Nominal Power (kVA) Maximum Line Cable lenght (m) Proposed cable cross section (mm ²)	0,029
Maximum Line Cable lenght (m) 21 Proposed cable cross section (mm²) 91 Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,9 WATER COOLING Number of pancakes per pole 330	Maximum Line Cable lenght (m) Proposed cable cross section (mm ²)	35
Proposed cable cross section (mm²) 9! Proposed Output PS Current (A) 330 Proposed Output PS Voltage (V) 130 Proposed Output PS Power (kVA) 42,0 WATER COOLING Number of pancakes per pole 3	Proposed cable cross section (mm ²)	20
Proposed Output PS Current (A) 33i Proposed Output PS Voltage (V) 13i Proposed Output PS Power (kVA) 42,9 WATER COOLING 13i Number of pancakes per pole 13i		95
Proposed Output PS Voltage (V) 13i Proposed Output PS Power (kVA) 42,9 WATER COOLING Number of pancakes per pole 3i	Proposed Output PS Current (A)	330
Proposed Output PS Power (kVA) 42,5 WATER COOLING Number of pancakes per pole	Proposed Output PS Voltage (V)	130
WATER COOLING Number of pancakes per pole	Proposed Output PS Power (kVA)	42,9
Number of pancakes per pole	WATER COOLING	
	Number of pancakes per pole	3
Number of pancake circuits	Number of pancake circuits	6
Number of series circuits	Number of series circuits	2
ΔT water (°C) 1!	ΔT water (°C)	15
Maximum Water flow (m ³ /s) 0.11	Maximum Water flow (m ³ /s)	15
		0.117
Maximum Water velocity (m/s) 1,5	Maximum Water velocity (m/s)	0.117

			IRON			
V (mm3)	PACK FAC		d (kg/dm3)		Weight (kg)	
6,75E+07		0,96		7,85		509
			COILS			
V (mm3)	FILL FAC		d (kg/dm3)		Weight (kg)	
9.46E+06		0,59		8,9		50

Iron lamination dipole

- Magnetic and electro-thermical design, mechanical drawings completed
- Construction started
- Power supply specifications and tender completed; ramping +stabilization within ~100 ms







DP-01 Timing







Pulsed dipole construction







Laser cutElectron Discharge Machining CMM shape measurementUnder evaluation by the metrology service @ LNF



First coil









New DC dipoles



GENERAL DATA	
Beam energy (MeV)	921
Curvature radius (m)	1,8
Gap (mm)	35
Pole width at the gap (mm)	190
Pole width at the yoke (mm)	220
Nominal flux density (T)	1,7056
Bending angle (deg)	45,00
N per pole (turns)	120
Iron Width (mm)	735
Overall Width	780
Overall Height (mm)	503
Overall Lenght (mm)	1672
Good Field Region (mm)	±15
Field quality (ΔB/B)	4,29E-04
Integrated Field quality (ΔΙΒ/ΙΒ)	3,78E-04
Total weight (kg)	4006
ELECTRICAL INTERFACE	
Conductor dimension	9.5x9.5 Ф5.5
Nominal Current (A)	262
Nominal Resistive Voltage (V)	72
Rtot (Ω)	0,276
Nominal inductance (H)	0,423
Nominal Voltage on magnet (V) with a 10 s raising time (V)	83
Nominal Power (kVA)	22
Maximum Line Cable lenght (m)	20
Proposed cable cross section (mm ²)	95
Proposed Output PS Current (A)	280
Proposed Output PS Voltage (V)	95
Proposed Output PS Power (kVA)	26,6
WATER COOLING	
Number of pancake per pole	6
Number of Turn per pancake	(10 H 2 V)
ΔT water (°C)	15
Maximum Water flow (m ³ /s)	3,44E-04
Maximum Water velocity (m/s)	1,21
Maximum ΔP (bar)	3.82

		IRON		
V (mm3)	PACK FAC	d (kg/dm3)		Weight (kg)
3,99E+08	1		7,86	3140
		COILS		
V (mm3)	FILL FAC	d (kg/dm3)		Weight (kg)
9,5E+07	0,599		8,9	506

Iron core dipoles

- Magnetic and electro-thermical design, mechanical drawings completed
- Power supplies specifications and tender completed







New quadrupoles

	Unit	Value		
MAIN SPECIFICATION				
Nominal Gradient	T/m	20		
Bore	mm	45		
Magnetic length	mm	200		
Pole width	mm	45		
Integrated quality (r=15mm)		5 10 ⁻³		
COIL DATA				
Conductor dimensions	mm x mm	5x5 bore φ 3mm		
Number of turns per pole		46		
Water pressure drop	bar	3.5		
ELECTRICAL INTERFACE				
Nominal Current	А	88		
Magnet Resistance	mΩ	110		
Magnet Inductance	mH	22		
Nominal Voltage	v	11		
Power	кw	0.97		



Iron core quadrupoles

- Magnetic, electro-thermical, design completed
- Detailed mechanical drawings almost completed
- Power supplies specifications and tender completed







- Internal Civil engineering and shielding March 2018.
- Pulsed dipole end of April 2018.
- New line September 2018
- Quadrupoles end of September 2018.
- Human resources: 1FTE up to Nov. 2018







Photon tag

- The complete redesign of the BTF facility, including the installation of a second user beam-line, opened the possibility of re-engineering the photon tagging system with the objective of making it again available to the detector development community.
- The system has been re-engineered, the tagging modules configuration revised and the failing or missing readout electronics and PC revamped.
- All components have been installed and tested and are ready to be used in the new C-shaped magnet of the new BTF line.







Figure 1 - MOD2INPUT



Figure 5: New VME board compact communication board, cabled to the tagging modules via flat cables, and the VME side of the SBS (Bit3) controller, installed in the BTF experimental area.







- The doubling of BTF is ongoing.
- Beam reserved to PADME on line-1
 from April to August
- Open call in second half of 2018 for last part of 2018/2019













Timing

- DAFNE reference $Ø_4$ for the injection systems
- Conditioned Ø₄ -> DELAYED LINAC SYS SIGNAL moves all the LINAC stuff together to match ACCUMULATOR phase)
 - DELAYED GUN SIGNAL -> LINAC SYS REFERENCE (once optimized, not moved for months)
 - BTF REFERENCE -> USER needs DELAYED LINAC SYS

 \rightarrow WE ARE WORKING in STATIC LINAC+BTF TRIGGERING SCHEME

Some Jitter contribution (see also AMY and UA9 experiences)

- LINAC SYS reference jitter (rms, 10ps, our best measure)
- LINAC GUN jitter (100ps)
- BTF STANFORD DDG535m single channel jitter (rms, 50ps + 0.01ppm of the channel delay) .











With 1.1×10^{11} n in the target:

- 8.8×10⁸ n/cm²/s exiting from the target
- $1.87 \times 10^{10} \text{ }\gamma/\text{cm}^2/\text{s}$ exiting from the target

d (m)	×10 ⁻⁷ n/cm²/pr
0.5	58
1	15
1.5	8

At 1.5 m distance: <u>Total</u> neutron flux: 8×10⁻⁷ n/cm²/pr ±3%

Flux = **4.5×10⁵ n/cm²/s** Equivalente dose = 45 mSv/h

d (m)	×10 ⁻⁵ γ/cm²/pr
0.5	63
1	5.7
1.5	1

At 1.5 m distance <u>Total</u> photon flux = 1×10^6 γ/cm²/s







Neutron electro-production



Evaporation peak + fast neutrons shoulder

- At full linac power: 10¹³ e/s
 - to be compared e.g. with nELBE, N=6.10¹⁵ e/s
- Swanson estimate
 - 9.3.10¹⁰ Z^(0.73±0.05) n/s kW⁻¹
 - 2.15 ·10¹² n/s kW⁻¹ for Tungsten
- Optimizing the target configuration can (slightly) improve the yield:
 - n@BTF optimized target: 2.75 ·10¹² n/s kW⁻¹
 - 0.218 n/pr (over 4π and all spectrum)
- In our case the main limitation will always be the intensity delivered onto the target







PADME experiment





- CSN I full approval for 1,350 kEuro for 2016-2018
- Magnet from CERN (OK, being measured now)
- 500 BGO crystals from former L3 experiment
- Calorimeter construction starting in Spring 2016
- Active diamond target being developed in Lecce
- Scintillating bars positron veto being developed in Sofia
- Interest from Hungarian group

INFN

Collaboration with Cornell starting this summer



