

EUROPEAN
PLASMA RESEARCH
ACCELERATOR WITH
EXCELLENCE IN
APPLICATIONS




WP15 Diagnostics

A. Cianchi (University of Rome Tor Vergata)

N. Delerue (LAL)

On behalf of EuPRAXIA WP15 diagnostics group



This project has received funding from the European Union's Horizon 2020 research and innovation programme under grant agreement No 653782.



EUPRAXIA: MILESTONE REPORT

*Doc. Identifier:
MS 5.4
Date: February 20, 2019*



Project Number: 653782

Project Acronym: EuPRAXIA

Project title: European Plasma Research Accelerator with eXcellence In Applications

Milestone Report

M 5.4 Definition of diagnostics before and after the plasma channel

- Contributions from:
 - CEA
 - CNRS
 - Cockroft
 - DESY
 - ELI-Beamlines
 - INFN
- Cost estimation
- Starting point

Introduction



**Diagnostics deliverable:
done**

However, we swept
some dirt under the
carpet...

HOPA beamlines still out
of the report



**More than a talk this is
an open space to collect
and to address
questions**



**Hopefully also to find
the answers...**

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven
- Quite compact design and reasonably integrated in the beam optics (update needed!)

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven
- Quite compact design and reasonably integrated in the beam optics (update needed!)
- Reasonable multi-shot solutions exist already, but single shot will be much more interesting

Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven
- Quite compact design and reasonably integrated in the beam optics (update needed!)
- Reasonable multi-shot solutions exist already, but single shot will be much more interesting
 - R&D needed


Some important points

- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven
- Quite compact design and reasonably integrated in the beam optics (update needed!)
- Reasonable multi-shot solutions exist already, but single shot will be much more interesting
 - R&D needed
- Today not yet a solution for slice energy spread even in a conventional accelerator

Some important points


- Two sets of diagnostics beamlines, one for commissioning phase and one for normal operation
- Capture the beam as soon as possible after plasma, diagnostics less important than beam optics.
- Betatron radiation from plasma
- Basic layout done for all the possibilities, plasma injector, RF injector, laser driven, beam driven
- Quite compact design and reasonably integrated in the beam optics (update needed!)
- Reasonable multi-shot solutions exist already, but single shot will be much more interesting
 - R&D needed
- Today not yet a solution for slice energy spread even in a conventional accelerator
- Driver removal still an open point, we would like to have the beam particles after this stage.

Today at 20:30 near bar area




Integration

- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space




Integration

- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space
- Pumping is not yet considered




Integration

- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space
- Pumping is not yet considered
- So far this machine is correctors free




Integration

- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space
- Pumping is not yet considered
- So far this machine is correctors free
- A cad drawings will be very useful to define better the line.




Integration


- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space
- Pumping is not yet considered
- So far this machine is correctors free
- A cad drawings will be very useful to define better the line.
- Is it too much for a CDR?




Integration


- So far we just put our elements in a reasonable way, using real dimensions, and leaving “enough” space
- Pumping is not yet considered
- So far this machine is correctors free
- A cad drawings will be very useful to define better the line.
- Is it too much for a CDR?
- However sooner or later we need it!








A better integration with beam optics is needed, spectrometer problem





















- Cavity BPMs seems to be the best choice for the trajectory but what's about beam position instability?
- Can we have 6 mm aperture?
- Turbo ICT seems to be a good choice for the charge, they can measure down to fC range, but what's about their response to EMI in a laser-plasma environment?

Charge
open
points



Weingartner, Raphael, et al., Physical Review Special Topics Accelerators and Beams 15.11 (2012): 111302

Barber, S. K., et al., Physical Review Letters 119.10 (2017): 104801.

F Li et al 2018 Plasma Phys. Control. Fusion 60 014029

F. Li et al, Plasma Physics and Controlled Fusion 60, 044007 (2018)

- R&D is in progress in different directions
 - CERN is developing Cherenkov diffraction radiation
 - SPARC_LAB is developing optical pepper pot
 - Still open room for high energy pepper pot
 - Multiple screens with plasma lenses

Longitudinal measurements



Are there really already developed single shot diagnostics?



Or maybe there are only proof-of-principle experiment?

Single shot CTR or CSP are not yet ready, experiments are ongoing
 X-band TDS are not yet so widespread and require careful tuning to be considered state-of-art

- Betatron radiation overlap between driver and witness
- Reduced possibility to measure the driver alone after the interaction
- No chance to distinguish driver-witness inside the machine (trajectory/charge), only in few points with dispersive (time or energy)...->

Main
problems
beam
driven

- Give us an evaluation of the different instabilities that we likely have to face

- Give us an evaluation of the different instabilities that we likely have to face
- Clearly define the driver (laser/beam) removal

- Give us an evaluation of the different instabilities that we likely have to face
- Clearly define the driver (laser/beam) removal
- Give us the particles distributions

- Give us an evaluation of the different instabilities that we likely have to face
- Clearly define the driver (laser/beam) removal
- Give us the particles distributions
- Implement the diagnostics layout in a CAD

- Give us an evaluation of the different instabilities that we likely have to face
- Clearly define the driver (laser/beam) removal
- Give us the particles distributions
- Implement the diagnostics layout in a CAD
- More details about HOPA beamlines

- Give us an evaluation of the different instabilities that we likely have to face
- Clearly define the driver (laser/beam) removal
- Give us the particles distributions
- Implement the diagnostics layout in a CAD
- More details about HOPA beamlines
- Support a program of R&D for EuPRAXIA components or help in having machine time (**D**iagnostics **C**luster for **E**upraxia)

- Thank you for your attention

- Longitudinal measurements
 - X band TDS and comparison on the same accelerator with others single shot measurements based on coherent radiation
- Transverse emittance
 - Test single shot devices with high brightness conventional machine
 - Test single shot device with high brightness plasma accelerator