Particle identification with fast timing detectors at future Higgs factories

DPG conference T 44.1 22 March 2022

Bohdan Dudar^{1, 2}, Jenny List¹, Ulrich Einhaus¹
¹Deutsches Elektronen-Synchrotron, ²Universität Hamburg













2020 Update of the European strategy for particle physics


3 |


High-priority future initiatives


A. An electron-positron Higgs factory is the highest-priority next collider. For the longer term, the European particle physics community has the ambition to operate a proton-proton collider at the highest achievable energy. Accomplishing these compelling goals will require innovation and cutting-edge technology:


link

Major candidates for the future Higgs factories












Major candidates for the future Higgs factories




Particle identification with time-of-flight













Particle identification with time-of-flight



Particle identification with time-of-flight



Long-term goal is to understand: How beneficial TOF pID would be? Is it worth the investment?

Momentum calculation

We calculate momentum from the curvature Ω :


$$p = e^{\frac{|B_z|}{|\Omega|}} \sqrt{1 + \tan^2 \lambda}$$





Momentum calculation

We calculate momentum from the curvature Ω :

$$p = e^{\frac{|B_z|}{|\Omega|}} \sqrt{1 + \tan^2 \lambda}$$








Momentum calculation

We calculate momentum from the curvature Ω :

$$p = e^{\frac{|B_z|}{|\Omega|}} \sqrt{1 + \tan^2 \lambda}$$



BUT curvature may significantly change due to energy loss along the track!



IMPROVED: calculate momentum at every tracker hit and use harmonic mean for particle ID

$$p_i = e \frac{|B_z|}{|\Omega_i|} \sqrt{1 + \tan^2 \lambda_i}$$

$$p = \sqrt{\langle p^2 \rangle_{HM}} = \sqrt{\sum_{i=0}^{n} \ell_i / \sum_{i=0}^{n} \frac{\ell_i}{p_i^2}}$$

22 March 2022

credit goes to Winfried A. Mitaroff

More info on track paramters Ω , φ , tan λ , z

link

Track length calculation

Simple assumption: track is a helix

$$\ell_{\rm track} = \frac{|\varphi_{\rm end} - \varphi_{\rm start}|}{|\Omega|} \sqrt{1 + \tan^2 \lambda}$$



Track length calculation

Simple assumption: track is a helix

$$\ell_{\rm track} = \frac{|\varphi_{\rm end} - \varphi_{\rm start}|}{|\Omega|} \sqrt{1 + \tan^2 \lambda}$$



- Relies on constant momentum along the track
- Does not work for curly tracks



Track length calculation

Simple assumption: track is a helix

$$\ell_{\rm track} = \frac{|\varphi_{\rm end} - \varphi_{\rm start}|}{|\Omega|} \sqrt{1 + \tan^2 \lambda}$$



BUT has similar limitations:

- Relies on constant momentum along the track
- Does not work for curly tracks

IMPROVED: iterate hit-by-hit and sum lengths between neighbor hits:

$$\ell_{\text{track}} = \sum_{i=0}^{n} \ell_i = \sum_{i=0}^{n} \sqrt{\left(\frac{\varphi_{i+1} - \varphi_i}{\Omega_i}\right)^2 + (z_{i+1} - z_i)^2}$$

credit goes to Winfried A. Mitaroff


link

15

More info on track paramters Ω , φ , tan λ , z

Results of improved mass reconstruction


Significant improvement in the endcap:



*plots assume perfect time resolution in the first ECAL layer

Results of improved mass reconstruction

Mild improvement in the barrel:




*plots assume perfect time resolution in the first ECAL layer

Each hit has:
x, y, z, t, E


Very smart algorithm () = time-of-flight



Each hit has: x, y, z, t, E



Bohdan Dudar, Ulrich Einhaus




No.

= time-of-flight

Yuzhi Che, Manqi Ruan link

6. Conclusion Scaling hit time · Arbor clustering module improves the resolution EM (hadronic) cluster time resolution by a factor of ~1.2 (1.4) Reduced Layer number The cluster time resolution is proportional to the intrinsic time resolution. All ECAL · Cluster time resolution is inversely proportional to the $\sqrt{N_{layer}}$ estimato · Alternative strategy: OSV estimator OSV estimator could improve the EM cluster TOF resolution by a factor of ~3.

Many analyses are ongoing...




BUT we have <u>very simplified</u> simulation of time measurement.

- no digitization
- $t_0 = 0$
- Only earliest MC contribution is considered



BUT we have <u>very simplified</u> simulation of time measurement.


- no digitization
- $t_0 = 0$
- Only earliest MC contribution is considered




- Take only closest ECAL hit to the track
- smear its time with a Gaussian



Particle identification: separation power



Particle identification: efficiency & purity



Summary

- We have improved momentum and track length estimations that are crucial for particle identification with the time-of-flight
- We can achieve K[±] ID <u>efficiency > 92%</u> and <u>mis-tag rate < 8%</u> up to 6 GeV momentum using only single ECAL hit with <u>10 ps</u> hit time resolution
- Take away for the hardware: get below 30 ps TOF resolution (as close to 10 ps as possible)

Summary

- We have improved momentum and track length estimations that are crucial for particle identification with the time-of-flight
- We can achieve K[±] ID <u>efficiency > 92%</u> and <u>mis-tag rate < 8%</u> up to 6 GeV momentum using only single ECAL hit with <u>10 ps</u> hit time resolution
- Take away for the hardware: get below 30 ps TOF resolution (as close to 10 ps as possible)

TODOs

Long-term goal is to understand:
How beneficial TOF pID would be?

<u>Is it worth the investment?</u>

