



# CERN High luminosity LLRF project Crab-Cavities

Reported by **G. Hagmann**

Contributions from P. Baudrenghien, R. Calaga, J. Egli,  
L. Giacometti, T. Mastoridis, E. Yamakawa, D. Valuch

MTCA workshop 2023, December 5, 2023

# Overview

- 1) HL-LHC projet
- 2) Specifications for LLRF
- 3) LLRF Architecture
  - Feedback loop
  - Master Reference
  - RF Modulation
  - Clock Distribution
- 4) Cavity-Controller
  - Cavity-controller (PoC)
  - Amplitude & Phase feedback (PoC)
- 6) Master plan
- 7) Conclusion

# HL-LHC project - Introduction

- The High-Luminosity LHC (HL-LHC) upgrade planned operation from **2029** onwards [4]
- Upgrade goal of **tenfold increase of the integrated luminosity**:
  - Expected cumulative LHC integrated luminosity by end 2024: 350 fb-1
  - HL-LHC integrated luminosity: 250 fb-1 per year, 3000 fb-1 (12 years)
- Increasing the luminosity by
  - **Doubling the intensity** per bunch ( $2.2 \times 10^{11}$  p+ per bunch)
  - **Reducing the transverse beam size** at the IP ( $\beta^*$  reduction)
- Issue with the beam current increase
  - Long range beam-beam interaction at the collisions Intersect Points
  - Reduced by increasing the **full crossing angle** from 320  $\mu$ rad to **500  $\mu$ rad**
- key upgrades for increasing luminosity
  - LHC triplet magnet upgrade
    - Current triplet aperture limits the potential  $\beta^*$  Low  $\beta$  inner triplet quadrupoles installed
  - Super-conducting Crab-cavities for LHC Point 1 (P1 - ATLAS) and LHC Point 5 (P5 - CMS)
    - Recovers part of the luminosity lost by crossing angle, via a **380  $\mu$ rad full crabbing angle**.




Fig – Variation of the geometrical luminosity reduction factor with  $\beta^*$  [4]

# HL-LHC project - Crab-Cavities

- Two types of Crab-Cavities



Double **Q**uarter **W**ave (DQW) resonator,  
Crabbing in vertical plane  
(IP5, CMS)



**R**F **D**ipole (RFD),  
crabbing in horizontal plane  
(IP1, ATLAS)




Fig – DQW Cavity and cryomodule (vertical crabbing)

$f_0 = 400 \text{ MHz}$   
 $V_T = 3.4 \text{ MV/cavity}^*$   
( $E_p, B_p < 40 \text{ MV/m}, 70 \text{ mT}$ )  
Beam aperture = 84 mm  
RF power = 50 kW-CW\*\*  
Operating Temp = 2 K




Fig – RFD Cavity and cryomodule (horizontal crabbing)

\*Engineering spec: 4.1 MV dressed for 20% margin  
\*\* Required for for beam off-centred by 1 mm

# HL-LHC project - layout

- 16 Crab-Cavities (SR4)
  - 4 cavities on each IP side (2 per beam)
- RF frequency sweeping
  - Acceleration ramp
  - RF distribution from point 4
- Based on White-Rabbit network
  - RF over White-Rabbit (fiber optics)
  - Master REF locked on WR




Fig – HL-LHC layout [2]

# HL-LHC project - layout




Fig – HL-LHC point 1 or 5 underground layout [1] . Top view

# Specifications for LLRF

- Cavity Impedance [5]:
  - Strong transverse impedance at the fundamental:
  - Four cavities per plane, per beam  $\rightarrow 4 \cdot 10^9 \Omega/m$
  - **Impedance reduction at fundamental by 1000 [5]**
  
- RF noise
  - Increases the transverse emittance (luminosity reduction).  
**Budget:** 2%/hour EMG<sup>1</sup> [14]
  - **Requirements:** phase/amplitude noise reduced to **-151 dBc/Hz** at 3 kHz offset from carrier (400 MHz) [11].
  - **Target:**
    - **-143 dBc/Hz @ 3 kHz offset [11]**  $\rightarrow$  7.6 %/hour EGR<sup>1</sup>
    - Mitigation via CC phase/amplitude fdbk for the extra factor 10 [7]




Fig – HL-LHC transverse impedance including crab-cavities fundamental mode [5] .




Fig – LHC ACS cavities and Crab-cavities SSB phase noise [11]

<sup>1</sup> Emittance Growth Rate

# Specifications for LLRF

## Crabbing closure

- Cavity phase on bunch core. Phase offset  $\rightarrow$  transverse displacement ( $\Delta x$  or  $\Delta y$ ) of bunch core
- **Coherent phase shift Requirement:  $<100\text{ps}$  phase error ( $14.4^\circ$ )** [1] (2% peak luminosity reduction)
- **In Coherent phase shift Requirement :  $<15\text{ps}$  phase error ( $2^\circ$ )** [1] (1% peak luminosity reduction)
- Precise crabbing-uncrabbing voltage ( $V_\Sigma$ )
- Counter-phasing on both side of the IP during filling/ramping ( $V_\Sigma=0$ )
- **Requirements:**
  - Voltage amplitude error = t.b.d

## Single-cavity failure

- Amplifier trip, quench/breakdown, multi-packing  $\rightarrow$  uncontrolled voltage
- **Requirements:**
  - Beam dump within 3 turns ( $\sim 270\mu\text{s}$ )
  - Compensation in the other cavities to track the uncontrolled voltage and limit the damage during the 3 turns till dump.
  - Global quality control (MIMO)




Fig – Identical phase shift for colliding bunches  $\phi_1=\phi_2$   
Partial crabbing [1]




Fig – Phase offset leading to transverse displacement on one beam only [16]



# LLRF Architecture - Feedback loops

- Power amplifier: IOT
- Self-Excitation Loop + Tuning loop
  - We must keep the cavity on-tune the entire LHC fill (filling/ramping/collision)
- Polar-loop
  - Slow regulation around the amplifier (Gain&phase drift, reduce amplifier noise)
- RF feedback
  - Control cavity field + Impedance reduction
    - **Fast loop around cavity-amplifier, BW≈260kHz**
    - **Slow global loop regulating the vector sum: crabbing-uncrabbing voltages**
- Crab-cavity amplitude & phase noise feedback
  - Beam phase & tilt measurement
  - Cavity phase tracking bunch core




Fig – Crab Cavity Low-Level RF block diagram [11]




Fig – Crab-cavity noise feedback [10]



# LLRF Architecture - RF Modulation

- Synchrotron → RF ramp
  - RF = 400.7842 to 400.7896MHz (+5.4kHz)
  - Feedback BW ≈ 260kHz
  
- Up/Down-mixing for RF input
  - Single-side band transmitter scheme
  - LO at fixed frequency, IF freq sweeping
  - LO=REF=RF-IF, **IF≈13MHz**
    - Optimized for IF aliasing, RF noise
  - **Clock=125MHz**
    - Optimized for latency
  
- LO leakage & images rejection
  - DAC's (I&Q) calibration
  - External BPF (add latency)






Fig – RF up/down modulation scheme

# LLRF Architecture - Clock Distribution

new eRTM15 to be developed  
(distribution only)



Standalone unit for  
«Master REF»  
(space, mechanical noise,  
temperature stability)

reuse eRTM14  
(EDA-03849)

Fig – Master Reference & eRTM diagram



# Crab-Cavity phase/Amplitude feedback (PoC)

- Pickup front-end
  - Analog pre-processing for Bunch phase/tilt
- Average bunches phase
  - Crab-cavity phase tracking bunch core
- Bunch-per-bunch phase & tilt measurement
  - Feedback to Crab-Cavity voltage setpoint (RF noise reduction)




Fig – HL-LHC Beam phase & tilt measurement, alternative with dedicated AMC+RTM

# Crab-Cavity phase/Amplitude feedback (PoC)

- Alternative solution with dedicated AMC & RTM
- MTCA backplane point-to-point Gbit link
- Inspired from the LHC Beam position measurement system [17]
- Requires new RTM




Fig – HL-LHC Beam phase & tilt measurement, alternative with dedicated AMC+RTM

# Master plan




Fig – HL-LHC schedule [13]

Today

Start LS3

Beam

5 years

# Conclusion

- HL-LHC targets a tenfold luminosity increase
- Crab-Cavities will recover the head-on collision from the large crossing angle (380  $\mu\text{rad}$  vs. 500  $\mu\text{rad}$ )
- Challenging LLRF specifications
  - Transverse Impedance reduction
  - RF noise: max 2 %/h transverse emittance growth, HW to be designed? (low noise receiver + CC fdbk)
- Architecture
  - White-Rabbit based
  - MTCA platform
  - Master Reference (clock, LO generation) + eRTM

# References

- [1] E. Yamakawa et al., Luminosity reduction caused by phase modulations at the HL-LHC crab cavities, NIMA 2018, <https://www.sciencedirect.com/science/article/pii/S0168900218310325>
- [2] HL LHC layout, <https://voisins.web.cern.ch/en/high-luminosity-lhc-hl-lhc>
- [3] J. Gill, RF Signal Distribution over WR, Nov. 2019, BE seminar [https://indico.cern.ch/event/865008/attachments/1949767/3236439/BE\\_seminar\\_WR\\_Applications-RFoWR.pdf](https://indico.cern.ch/event/865008/attachments/1949767/3236439/BE_seminar_WR_Applications-RFoWR.pdf)
- [4] I. Béjar Alonso et al., **High-Luminosity Large Hadron Collider (HL-LHC)**, technical Design Report, CERN-2020-010, <https://doi.org/10.23731/CYRM-2020-0010>
- [5] L. Giacometti et al., **Mitigation strategies for the instabilities induced by the fundamental mode of the HL-LHC crab cavities**, HB 2023, CERN Oct 2023, <https://indico.cern.ch/event/1138716/>
- [6] P. Baudrengnien, T. Mastoridis, **Transverse emittance growth due to rf noise in the high-luminosity LHC crab cavities**, Physical review accelerator and beams, October 2015, <https://doi.org/10.1103/PhysRevSTAB.18.101001>
- [7] P. Baudrengnien, T. Mastoridis, **Transverse Emittance Growth due to RF Noise in Crab Cavities: Theory, Measurements, Cure, and High Luminosity LHC estimates** [Manuscript submitted for publication], CERN Geneva, CalPoly University San Luis Obispo, June 2023.
- [8] R. Calaga, “**Crab Cavities for the High-luminosity LHC**”, in Proc. SRF’17, Lanzhou, China, Jul. 2017, pp. 695-699., <https://doi.org/10.18429/JACoW-SRF2017-THXA03>
- [9] T. Mastoridis et al., **Cavity voltage phase modulation to reduce the high-luminosity Large Hadron Collider rf power requirements**, PRAB Oct 2017 [Phys. Rev. Accel. Beams 20, 101003 \(2017\)](https://doi.org/10.1016/j.nucphys.2017.10.003) - [Cavity voltage phase modulation to reduce the high-luminosity Large Hadron Collider rf power requirements \(aps.org\)](https://doi.org/10.1016/j.nucphys.2017.10.003)
- [10] P. Baudrengnien, T. Mastoridis, **Crab Cavity RF Noise Feedback and Transverse Damper Interaction**, CERN-ACC-NOTE-2019-0006, CERN Feb 2019, <https://cds.cern.ch/record/2665950>
- [11] P. Baudrengnien, T. Mastoridis, **HL-LHC Crab cavity Field Regulation and Resulting RF Noise**, CERN-ACC-NOTE-2023-0006, CERN May 2023, <https://cds.cern.ch/record/2859258/>
- [12] P. Baudrengnien, **LHC & SPS RF Controls for Crab Cavities**, LHC-CC11, 5<sup>th</sup> Crab cavity workshop, CERN, Nov 2011, <https://indico.cern.ch/event/149614>
- [13] R. Calaga, Status of WP4 crab cavities and RF, 13<sup>th</sup> HL-LHC Collaboration Meeting, Vancouver (CA), Sept 2023, <https://indico.cern.ch/event/1293138>
- [14] E. Metral et al., **Update Of The HL-LHC Operational Scenarios For Proton Operation**, CERN-ACC-NOTE-2018-0002, CERN January 2018, <https://cds.cern.ch/record/2301292>
- [15] S. Fartoukh et al., **LHC Configuration and Operational Scenario for Run 3**, CERN-ACC-2021-0007, CERN November 2021, <https://cds.cern.ch/record/2790409>
- [16] P. Baudrengnien, **Cavity Control**, LHC-CC13 6<sup>th</sup> LHC Crab Cavity Workshop, CERN Dec 2013, <https://indico.cern.ch/event/269322>
- [17] D. Valuch, Very Low Noise Receiver Technology for Digital Beam Position and Phase Measurement, LLRF22 workshop, Contribution ID 80, Oct 2022 Brugg-Windisch, Switzerland, <https://indico.psi.ch/event/12911/contributions/38423/>
- [18] G. Hagmann, **HL-LHC Crab-Cavities LLRF project**, Oct 2023, Gyeongju South-Korea, <https://www.indico.kr/event/29/contributions/411/>

# Clock Distribution - SIS8300KU+DWC8VM1 example




Fig – Clock distribution from eRTM to ADC& DAC on SIS8300KU

RTM  
DWC8VM1LF