

International
Muon Collider
Collaboration



Funded by the European Union (EU). Views and opinions expressed are however those of the author only and do not necessarily reflect those of the EU or European Research Executive Agency (REA). Neither the EU nor the REA can be held responsible for them.




10 TeV Muon Collider: MDI update: pair production and nozzle tip studies

D. Calzolari (CERN - SY/STI/BMI) on behalf of the IMCC


April 2024

Outline

- **Machine-Detector Interface (MDI):**
 - Geometry of the interaction region
 - Current version of the nozzle
- **Luminosity:**
 - Beam-beam effects and luminous region
- **New incoherent pair production sample**
- **Electron fluences in the first tracker layers:**
 - Incoherent pair production
 - Muon decay background



MDI: geometry of a 10 TeV collider






International
UON Collider
Collaboration



Luminosity: some consideration

- As shown during the annual meeting (see [this presentation](#)), the luminosity is enhanced due to the pinch effect.
- S. P. Griso raised another point: what is the extension of the luminous region? In other words, where are collision happening?
- I calculated the luminous region with and without beam effects. In all cases, the interactions will occur in the very close proximity of the IP.

Important hourglass
effect: β depends on s




Tiny luminous region:
 $\sigma \ll 1 \text{ cm}$





Incoherent pair production: new sample

- With Guinea-Pig, I produced a new incoherent pair production background sample.
- The new software version allows to fully simulate the interaction between muons, while in the past the interactions were simulating with a mass scaling of the electrons.
- With higher virtuality, pairs can have more kinetic energy



Incoherent pair production: new sample

- With Guinea-Pig, I produced a new incoherent pair production background sample.
- The new software version allows to fully simulate the interaction between muons, while in the past the interactions were simulating with a mass scaling of the electrons.
- With higher virtuality, pairs can have more kinetic energy







Incoherent pair production: fluences in trackers

International
UON Collider
Collaboration

- A large fraction of electron (positrons) are not intercepted by the nozzle, and will travel in the trackers without shielding.
- To calculate these fluences, I modeled the nozzle as a blackbox to observe only the "direct" fluences






Incoherent pair production: fluences in trackers


International
UON Collider
Collaboration

- A large fraction of electron (positrons) are not intercepted by the nozzle, and will travel in the trackers without shielding.
- To calculate these fluences, I modeled the nozzle as a blackbox to observe only the "direct" fluences.
- With an higher field, the first double layer has a lower $e^{+/-}$ fluence and the second layer is spared

Electron/positron fluences with 3.57 T solenoid



Electron/positron fluences with 5 T solenoid






Incoherent pair production: fluences in trackers


International
UON Collider
Collaboration

- When including the contribution of the interactions with the nozzles, there is an additional fluence of secondary particles.
- The contribution from these secondary particles is not a dominant factor in the overall background

Electron/positron fluences with 3.57 T solenoid (w nozzle)



Electron/positron fluences with 5 T solenoid (w nozzle)







Incoherent pair production: comparison fields

International
UON Collider
Collaboration

- When including the contribution of the interactions with the nozzles, there is an additional fluence of secondary particles.
- The contribution from these secondary particles is not a dominant factor in the overall background

Electron/positron fluences with 3.57 T solenoid (w nozzle)






International
UON Collider
Collaboration


Decay background: nozzle tip influence

- To continue study the effect of the BIB on the first tracker layer, I simulated the fluence in case of different nozzle tip shapes



Decay background: nozzle tip influence

- To continue study the effect of the BIB on the first tracker layer, I simulated the fluence in case of different nozzle tip shapes.
- The geometry of the nozzle area is shown in figure. The only relevant parts are the nozzles and the trackers.
- No timecuts are applied (but can be done for future simulations)



Number of original decays simulated	Total number of secondaries produced	Secondaries produced per decay	Expected number of decays	Expected number of secondaries to nozzle area
9.22E+04	2.85E+07	308.77	1.18E+07	3.64E+09




International
UON Collider
Collaboration


Decay background: nozzle tip influence

- Three possible configuration are shown
- For the 2 cm, the tip position cause a necking in the inner cone aperture. The results show that this should be avoided


Fluence with nozzle tip at 6 cm



Fluence with nozzle tip at 2 cm



Fluence with nozzle tip at 8 cm






International
UON Collider
Collaboration


Decay background: nozzle tip influence

- Three possible configuration are shown
- For the 2 cm, the tip position cause a necking in the inner cone aperture. The results show that this should be avoided


Fluence with nozzle tip at 6 cm



Fluence with nozzle tip at 2 cm




Fluence with nozzle tip at 8 cm




Decay background: nozzle tip influence

- The comparison between different nozzle tip position is shown. This time includes contribution from both beams.
- The results show better performances with larger gaps. This is advantageous also from the mechanical engineering perspective (larger relative tolerances)

Fluence with different nozzle tip distances




Fluence comparison (decay vs pair production)



Conclusions

- Guinea-pig software was used for the calculation of the luminous zone and the generation of the incoherent pairs.
- The **luminous zone** has very **small longitudinal size**. The real shape can be used for detector performance simulations to sample the "real" vertex position.
- **Incoherent pairs** with the new Guinea-pig version have **harder spectra and more abundant particle multiplicity**.
- **Solenoidal field intensity has an influence in the $e^{+/-}$ fluences**. Using a realistic magnetic field map is not strictly required for simulation within the tracker region.
- The **nozzle tip** has a strong influence on the electron fluences in the first tracker layers. A distance of **4 cm or more is required** to avoid EM showers reaching the detectors from the nozzle tip.



International
UON Collider
Collaboration



***Thank you
for your attention!***

Workflow in the IMCC

Machine-Detector
Interface: MDI


1. Lattice design

The magnet optics is computed via dedicated codes (e.g. MAD-X).

The output is a twiss file, containing the machine elements in a sequence

2. FLUKA geometry model

Via LineBuilder (LB), complex geometries are assembled in a FLUKA input file



3. BIB simulation

With the built geometry, a FLUKA simulation is run.

The position and momentum of the decay muons are sampled from the matched phase-space

Iteration with lattice design experts to mitigate the BIB

BIB data to detector experts

CERN STI/BMI is currently responsible for the geometry built at $\sqrt{s} = 3$ and 10 TeV