

# FLASH2020+

## Progress Review Meeting

Status of Photon Diagnostics / FEL beamline F10

Sven Toleikis for the P team  
Hamburg, 28.02.2025

# Overview I

- Recap of non-invasive measurement of

Pulse energy  
Wavelength  
Beam position



→ copies of current FLASH2 instruments

- Beam alignment tools

- Pulse length

→ Statistical methods @ PG, LOLA (for SASE), seed laser diagnostic (for seeding)

- New gas absorber

→ improve attenuation capability (x100)

- Polarization

→ (eTOF-Polarimeter “Ball-chamber”), OPIS (maybe delayed ?)

## *Postponed additional photon diagnostics & new challenges:*

- Spectral diagnostic for seeding  
Spectral information for users

→ New high-resolution VLS grating spectrometer  
geometrical/conceptual design finished

- Photon beam-based undulator alignment

→ K-Mono (XFEL design not 1:1 applicable)

- Atto-second pulse length diagnostics  
@FLASH2 only, not part of F2020+  
but high priority for PSC

→ angular streaking with advanced Cookie-box  
-> new photon diagnostic beamline FL28

# Recap of the photon diagnostics concept

Basically a copy of the existing FLASH2 tools

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length


# Recap of the photon diagnostics concept

Basically a copy of the existing FLASH2 tools

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length

## XGMD:

- absolute intensity (within ~5%)
- pulsed resolved up to 4.5 MHz
- non-invasive
- Improved XGMD design (in use at XFEL, LCLS, and SwissFEL)




# Recap of the photon diagnostics concept

Basically a copy of the existing FLASH2 tools

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length

**XGMD:** precise beam position (within  $\sim 10\mu\text{m}$ )



Ce:YAG crystals

# Recap of the photon diagnostics concept



Basically a copy of the existing FLASH2 tools

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length

## OPIS:


Wavelength determination with photoelectron spectroscopy 4 eTOFs at “magic angles”

- Central wavelength monitoring (within  $\sim 0.1\text{eV}$ )
- Diagnostic tool for FEL bandwidth, beam position, two-color operation
- Non-invasive



# Recap of the photon diagnostics concept

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length



or PG beamline in case  
a higher resolution is  
required

G. Brenner et al.,  
Nucl. Instr. and Meth A **635**, 99–103 (2011).




# Recap of the photon diagnostics concept

## Re-usage of existing components

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length

**XSEED spectrometer** in front of the absorber PS0 and V0 (J. Zemella)





# Recap of the photon diagnostics concept

Basically a copy of the existing FLASH2 tools

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length

We still need to gain experience with **OPIS** for online polarization measurements in the tunnel.  
Only 4 e-TOFs might be insufficient...



**OPIS**

# Recap of the photon diagnostics concept

## Using new concepts

- Intensity
- beam position
- spectral distribution
- polarization
- pulse length


Angle resolving spectrometer setup “**ball chamber**”.  
Idea is to check the reproducibility of the Apple-III undulator settings from time to time.






# Polarization Diagnostics @ FLASH2

- Ball chamber instrument at FL21 diagnostics beamline



# Polarization Diagnostics @ FLASH2

- Ball chamber instrument  
Measuring **angular distribution of photoelectron emission** of a certain photoelectron feature from 3rd harmonic



- Fit angular distribution formula

$$I(\theta) = \frac{\sigma}{4\pi} \left[ 1 + \frac{\beta}{4} \left[ 1 + 3 \cdot P_{lin} \cdot \cos(2(\theta - \varphi)) \right] \right]$$

- Stokes parameter  $P_{lin}$  of linear polarization tilt angle  $\varphi$  versus horizontal axis


$\beta(3h\nu)$  anisotropy parameter  
value needs to be known

$\sigma(3h\nu)$  PE feature ionization cross section  
value is relevant for choice of PE feature and signal strength





$I(\theta_{eTOF})$  Intensity measurement needs to be calibrated




# Polarization Diagnostics with Ball Chamber 01.03.2024 - Polarization Modes



$E_{\text{ACC}} = 880 \text{ MeV}$   
 $h\nu = 104.6 \text{ eV} / 313.8 \text{ eV}$




# Polarization Diagnostics with Ball Chamber 01.03.2024 - ABU gap scans




- 3<sup>rd</sup> harmonic signal intensity change along afterburner gap variation
- Determine/confirm the optimal gap value

**BALL:** Kr 3d photoelectrons






- Value of linear Stokes parameter P1 along afterburner gap variation

- Wavelength determination with photoelectron spectroscopy  
4 eTOFs at “magic angles”
  - Central wavelength monitoring (within  $\sim 0.1\text{eV}$ )
  - Diagnostic tool for FEL bandwidth, beam position, two-color operation
  - Non-invasive



## Simulation study on polarization measurement

- Mounting OPIS chamber with a different angular alignment for improved (linear) polarization diagnostics via photoemission anisotropy
- Optimal rotation angle:  $45^\circ$  (with CF160 adapting flanges)  
Acceptable rot. Angles:  $36^\circ/54^\circ$  (use bore circle position)



**Calibration and test measurements  
@ PTB in April 2025 (KW 16 & 17)**





# Recap of the photon diagnostics concept

Basically a copy of the existing FLASH2 tools



- Intensity
- beam position
- spectral distribution
- polarization
- pulse length (indirect)
- beam attenuation / filtering

Here, we have to rely on indirect measurements using a TDS like PolariX or LOLA then at FLASH1




# Attosecond- and Polarization Diagnostics FLASH 2020+

## First steps towards angular streaking




- Single-shot, non-invasive online diagnostics for time-energy structure and polarization.
- Mapping FEL pulse time structure on the angular coordinate of photoemission („hand of a clock“)
- Advanced setup (SpeAR – BMBF funded) in 2023 and adaptation for FLASH following at FL28
- ErUM-Pro TRANSALP project dedicated to a laser system (incl. postdoc) and instrumental advances for angular streaking @ FLASH


# New angular streaking pulse length diagnostic at FLASH 2.



# Diagnostics and beam transport concept for FLASH1




# Things we could not implement due to the reduced budget and limited resources






# Diagnostics and beam transport concept for FLASH1 (tunnel) - FL10

## Modell



# FLASH1 Experimental Hall („Albert-Einstein-Hall“)


BDA area





# FLASH1 Experimental Hall („Albert-Einstein-Hall“)

new FL11 beamline incl. OL beamlines and MOD hutch – currently in design phase!



# Installation schedule

Pretty tight schedule

Beginning of Jan.:

Originally planned start of installing components  
but components are late as well:  
still missing: two beamshutter chambers for FL10  
four THz chambers (manufactured outside): out of specs!!!

9	24.Feb - 2.Mar						Dump installation 😊
10	3.Mar - 9.Mar						Clean room installation – dump section
11	10.Mar - 16.Mar						Drilling holes for the FL10 and THz beamline
12	17.Mar - 23.Mar						Crane installation
13	24.Mar - 30.Mar						Crane installation
14	31.Mar - 6.Apr						<b>First pillars and granites installed in the tunnel</b> / Water / air pressure pipes installation?
15	7.Apr - 13.Apr						Installation of the cable trays beside the concrete pedestral?
16	14.Apr - 20.Apr						Installation of covers for the pedestral bay? Test of OPIS @ PTB
17	21.Apr - 27.Apr						Installation of covers for the pedestral bay? Test of OPIS @ PTB
18	28.Apr - 4.May	personal interlock test		intern personal interlock test	tunnel partially closed		Further installation and cabling and commissioning
19	5.May - 11.May	cool down					
20	12.May - 18.May	cool down					
21	19.May - 25.May	cool down					
22	26.May - 1.Jun						Further installation and cabling and commissioning
23	2.Jun - 8.Jun	personal interlock test		Generalprobe - IL-Test	tunnel partially closed		
24	9.Jun - 15.Jun						
25	16.Jun - 22.Jun						
26	23.Jun - 29.Jun						Alignment of BDA and tunnel lance – Differential pumping gas attenuator
27	30.Jun - 6.Jul						Close photon vacuum systems in the tunnel
28	7.Jul - 13.Jul	personal interlock test (TUV)		personnel interlock test (TUV)	tunnel partially closed		Commissioning of all components
29	14.Jul - 20.Jul			RF-gun conditioning (Fr - Su)	Fr,12:00-Mo,7:00: tunnel closed		
30	21.Jul - 27.Jul			RF-gun conditioning (Fr - Su)	Fr,12:00-Mo,7:00: tunnel closed		
31	28.Jul - 3.Aug			RF-gun conditioning (Fr - Su)	Fr,12:00-Mo,7:00: tunnel closed		
32	4.Aug - 10.Aug	Commissioning					Further things which needs to be done at FLASH2 before the start of beam operation:
33	11.Aug - 17.Aug	Commissioning with beam					

Further things which needs to be done at FLASH2 before the start of beam operation:

- Replacement of several ion gauges in the FL20 beamline (tunnel and exp. hall)
- Back-intallation of the FL2 SDU into the FL23/24 beamline
- Finalizing FL23M0 mirror chamber

# Installation schedule 2

## Still on the agenda – 2026...

- Tunnel: missing components of FL10: e.g. OPIS?, THz: PARC, missing FEL undulators, ...
- Building FL11 beamline, MOD1.BL, OL beamlines and FL11 exp. laser hutch
- Building FL28: Angular streaking setup for attosecond- and polarization diagnostics
- Further improvement of the optical pump-probe lasers: FLASH1 and FLASH2
- ...

### Reminder for the commissioning with FL1 seeded photons:

w/o FL11 + MOD1.BL

only

**FL12 (CAMP)**

**FL14 (PG2)**

**FL15 (TRIXS)**

but w/o pump-probe laser, but SDU at 13.5 nm  
only open port beamline, with PIGLET PP laser  
fixed endstation with PIGLET PP laser

are available!

# Summary

- Non-invasive measurement of
    - Pulse energy
    - Wavelength
    - Beam position
  - Beam alignment tools
  - Pulse length
  - New gas absorber
  - Polarization
- copies of current FLASH2 instruments
- Statistical methods @ PG, LOLA (for SASE), seed laser diagnostic (for seeding)
- improve attenuation capability (x100)
- eTOF-Polarimeter variant of the “Ball chamber” or OPIS

## *Postponed additional photon diagnostics & new challenges:*

- Spectral diagnostic for seeding  
Spectral information for users
  - New high-resolution VLS grating spectrometer geometrical/conceptual design finished
  - lead time from decision to installation ~3 years
- Photon beam-based undulator alignment
  - K-Mono (XFEL design not 1:1 applicable)
  - new R&D development necessary

# Acknowledgements

**FLASH2020+ is team work - WPs P1, P2, P3, P4, P5, P6, P7, S1, S4, A6 ...  
FS-BT, ZM, XFEL, TU Dortmund, HZB**

Christopher Behrens  
Yilmaz Bican  
Markus Braune  
Maciej Brachmanski  
Günter Brenner  
Markus Degenhardt  
Stefan Düsterer  
Siarhei Dziarzythski  
Wolfgang Freund (XFEL)  
Christopher Gerth  
Sören Grunewald  
Patrick NGotta  
Gesa Goetzke  
Wolfgang Helm (TU Dortmund)  
Mathias Hesse  
Markus Ilchen (FLASH-D/ TU Hamburg)  
Fini Jastrow  
Svea Kreis

Marion Kuhlmann  
Michael Krumrey (PTB)  
Carsten Mai (TU Dortmund)  
Thorsten Otto  
Rui Pan  
Steffen Palutke  
Elke Plönjes  
Evgeny Schneidmiller  
Horst Schulte-Schrepping  
Michael Sprung  
Markus Tischer  
Kai Tiedtke  
Sven Toleikis  
Rolf Treusch  
Nicole von Bargen  
Mikhail Yurkov  
Michael Walter  
....

# Thank you !

## Contact

**DESY.** Deutsches  
Elektronen-Synchrotron

[www.desy.de](http://www.desy.de)

Sven Toleikis

[sven.toleikis@desy.de](mailto:sven.toleikis@desy.de)

+49 40 8998 3827