

TDS measurements in the EuXFEL

Stuart Walker
DESY, 28.5.2025

HELMHOLTZ





Overview

Überblick


- The goal of this talk:
 - Enable you to do parasitic TDS measurements using either of the TDSs.
- Not the goal of this talk:
 - Insights into lots of implementation details.
 - A lengthy treatise on the full set of features of the TDS software.

Transverse Deflecting Structures

- Apply kick to a bunch linearly proportional to distance along bunch.
- Two modes at EuXFEL: parasitic and invasive
- Parasitic
 - Individual (streaked) bunches can be extracted from the bunch train using fast kickers.
 - TDS pulse typically longer than bunch spacing—adjacent bunches will be sent automatically to TLD.
- Invasive:
 - Put screen directly in line, limiting operation to 2 bunches.
 - Ideal for LPS measurements in dump sections.
- We have two TDSs: I1 (working) and B2 (hopefully working again imminently)



Parasitic Operation



The Measurement

Injector Off-Axis

Screen: **OTRC.58.I1**

Position: OFFAXIS

Beam Region: 1

Bunch Number: 101

Laser: Nepal XD1

Charge: 248 pC


Streak: 343.2 $\mu\text{m}/\text{ps}$

Fitted Beam Parameters

	Gaussian	RMS	Units
Bunch Length	5.54	4.79	ps
Time Resolution	0.439	0.53	ps
Intrinsic Beam Size	0.156	0.188	mm
Initial Streak	13.4	11.9	$\mu\text{m}/\text{ps}$

Peak Current


Reconstructed	17.09 A
First Crossing	16.62 A
Second Crossing	17.74 A




Finding the Tool

Wie man das Tool finden kann

- Beam Dynamics
 - → The I1 & B2 TDS Tool
- On some of the xfelbkr machines it can take up to a minute to start, but it does start, so be patient.
- I don't understand why.



Main Log



Diagnostic Section

Section: 71 82 101

Screen: GTRC.58.II Open Camera Expert

On Axis Off Axis Out

Position: OFFAXIS

Power Off Stop Images

Camera State: Powered and Acquiring Images

Special Bunch Midlayer

Last in Beam Region: Beam Region 3 Fast Kickers

Append Diag. Bunch: Bunch 101 TDS

Start Stop Pulses: 10000 IBFB AFF

Transverse Deflecting Structure

Phase: -132.00° Readback / + -131.91

Amplitude: 15.00% Readback / % 15.00

Voltage: 0.77 kV Readback / kV 0.77

Find Phase... Set Zero Crossing Zero Crossing: Not Set

Target

Go to ID... Undo ID and go to TLD... Change Optics...

Beam Loss Monitors

- BLM.58.II Reset
- BLM.60.II Reset
- BLM.63.II Reset
- BLM.66.II Reset



Machine State

Laser Heater Shutter: OPEN

IBFB LFF: ON

Screen: TDS


Fast Kickers



Time Calibration

Time Calibration

- We need to map pixels on the screen to time.
- To do this we adjust the phase of the TDS and see measure how much the beam moves on the screen. This is possible because we know the optics, the beam energy, and the TDS frequency.




Time Calibration

Reusing a previous time calibration

- Two choices:
 - Either you reuse a previous one (if it exists).
 - Or you measure it yourself.
- Time calibrations are per screen, per optics, per screen position, per energy, etc... so it's not so unlikely to have to remeasure it.

Calibration


Dispersion	0.00 m	Calculate Dispersion From Linear Optics
Energy	130.0 MeV	Read Energy from Machine
Bunch Charge	250.000 pC	Read Charge from Machine
Time Calibration	0 μmps^{-1}	No Time Calibration




Time Calibration

Measuring it yourself

- Measuring it yourself is slightly more involved, but still only should take a minute or so.






Setting the Phase Ranges

- Two TDS phase zero crossings, one phase either side of each crossing corresponding to the edge of the screen = 4 phases to be set.

1. Start the special bunch midlayer so that the beam is streaked on the screen.
2. Adjust the TDS phase to move the beam to one side of the screen. Press: Set First.
3. Adjust the TDS phase to move the beam to the other side of the screen. Press: Set Second.
4. Move to the other zero crossing with $+180^\circ$.
5. Adjust the TDS phase to move the beam to one side of the screen. Press: Set First.
6. Adjust the TDS phase to move the beam to the other side of the screen. Press: Set Second.




7. Press "Start Calibration".

Current Profile Measurement

Current Profile


- We must take beam images with the beam streaked in both directions, as well as unstreaked.
- This allows us reconstruct the current profile, extract the time calibration, and incoming tilt.

Screen: OTRC.58.I1																				
Position: OFFAXIS																				
Beam Region: 1																				
Bunch Number: 101																				
Laser: Nepal XD1																				
Charge: 248 pC																				
Streak: 343.2 $\mu\text{m}/\text{ps}$																				
Fitted Beam Parameters																				
<table border="1"><thead><tr><th></th><th>Gaussian</th><th>RMS</th><th>Units</th></tr></thead><tbody><tr><td>Bunch Length</td><td>5.54</td><td>4.79</td><td>ps</td></tr><tr><td>Time Resolution</td><td>0.439</td><td>0.53</td><td>ps</td></tr><tr><td>Intrinsic Beam Size</td><td>0.156</td><td>0.188</td><td>mm</td></tr><tr><td>Initial Streak</td><td>13.4</td><td>11.9</td><td>$\mu\text{m}/\text{ps}$</td></tr></tbody></table>		Gaussian	RMS	Units	Bunch Length	5.54	4.79	ps	Time Resolution	0.439	0.53	ps	Intrinsic Beam Size	0.156	0.188	mm	Initial Streak	13.4	11.9	$\mu\text{m}/\text{ps}$
	Gaussian	RMS	Units																	
Bunch Length	5.54	4.79	ps																	
Time Resolution	0.439	0.53	ps																	
Intrinsic Beam Size	0.156	0.188	mm																	
Initial Streak	13.4	11.9	$\mu\text{m}/\text{ps}$																	
Peak Current																				
<table border="1"><tbody><tr><td>Reconstructed</td><td>17.09 A</td></tr><tr><td>First Crossing</td><td>16.62 A</td></tr><tr><td>Second Crossing</td><td>17.74 A</td></tr></tbody></table>	Reconstructed	17.09 A	First Crossing	16.62 A	Second Crossing	17.74 A														
Reconstructed	17.09 A																			
First Crossing	16.62 A																			
Second Crossing	17.74 A																			




Current Profile Measurement

Finding the subwindow



Diagnostic Sections Utility

Main Log



Measurements

Write to XFEL e-Logbook...

Time Calibration

Calibration

Regenerate Axes

Display

Dispersion

0.00 m

Calculate Dispersion From Linear Optics

 Fix Aspect Ratio Subtract background Smooth Image

Auto Gain Control

Energy

130.0 MeV

Read Energy from Machine

Threshold

0.050

Read Rate

5Hz

Time Calibration

0 jumps

No Time Calibration

 Use Last Calibration



Accumulate Background

Background Images: 0

Background

Basic Workflow

1. Select BC2 or I1 (and screen, default is normally fine)
2. Select a bunch of interest.
3. Kick onto a screen without the TDS.
4. Try with the TDS on. hopefully the phase is approximately correct (if not you won't see anything). Else: adjust the TDS phase until you see the beam on the screen.
5. Get the TDS time calibration. Either:
 - Load the last, cached calibration (fast), or
 - measure it (again).
6. Check the phase.
7. Measure the current profile.



Losses



- One is naturally inclined to panic when one sees the panels go red with losses.
- EuXFEL designed for off-axis parasitic operation. Losses are OK!
 - Indeed, the EuXFEL was originally designed for permanent parasitic measurements of this kind.
 - The occasional current profile measurement is therefore *very* OK.
 - If we spend 10 minutes a day measuring the current profiles, that's still <1% of possible operation losses.
- Fast losses during the operation are masked in the MPS.
 - No train cuts if everything is configured correctly (Thomas Wamsat).
- One must nevertheless keep an eye on slow losses in the main panel.



Beam Loss Monitors

Beam Loss Monitors

Beam Loss Monitors



- List of typically relevant BLMs for each section
- Watch them fill up during streaking
 - reset them manually before they max out
 - Else beam will be lost!

Conclusion

- Parasitic current profile measurements with the TDS that are easy to do are here.
- Basic operation of the fast kickers and TDS should “just work”. Even if it doesn’t (sometimes), we’ll only get to “it just works” by repeated and routine usage.
- The only involved step is measuring the time calibration (which can also just be skipped if it’s been done before). General operation of the TDSs, measuring the current profile, etc., are all straight forward.
- There are other features that I’ve not touched upon (on-axis measurements, LPS measurements in dump sections, dump switching, optics changing, slice analysis).

Future

- The policy for usage: the EuXFEL is designed for it, so we just do them, and if we briefly disturb the users then so be it. Don't ask the RC to do them, instead inform them that we are going to do them.
- With the expected return of the BC2 TDS we would like to return to daily or near-daily current profile measurements for each beam region.
 - Goal should be operators do these daily routine measurements themselves, e.g. at 7am during tune up.
 - (Not my call, though)
- I encourage you to use it and give me feedback. I want you to use it and I will be happy also to show you personally how to use it. So just ask.

Backup

Subpanels

Area and Camera Control

Diagnostic Section


Section I1 B2 T4

Screen OTRC.58.I1

Position: OFFAXIS

Camera State: Powered and Acquiring Images

Special Bunch Midlayer




- Switch region (I1 or B2)
- Change screen
- Put screen in/off-axis or out (generally should be off-axis). Warning: will interrupt beam whilst moving
- Modify camera data taking state
- Camera expert button for more details

Subpanels

Special Bunch Midlayer

Last in Beam Region	Beam Region	1	<input type="button" value="Fast Kickers"/>
Append Diag. Bunch	Bunch	1	<input checked="" type="checkbox"/> TDS
<input type="button" value="Start"/>	<input type="button" value="Stop"/>	Pulses	10000
			<input checked="" type="checkbox"/> IBFB AFF



- Start/stop kicking
- Whether would fire TDS if started
- Extracted bunch selection.
 - “Append Diag. Bunch” puts one bunch at end of bunch train and kicks it.
 - A good button to click to quickly get some streaking!*
- IBFB AFF state (handled automatically, does not require manual use here)

*Careful when RF window is completely occupied.

Subpanels

TDS

Transverse Deflecting Structure

Phase **43.00°** Readback / ° **43.05**

Amplitude **10.00%** Readback / % **10.01**

Voltage **0.00MV** Readback / MV **0.00**

-180°

+180°

Set First Zero Crossing

Go To

Not Set



Find Phase...

Set Second Zero Crossing

Go To

Not Set

Target



Measurements

Write to XFEL e-Logbook...

Time Calibration

Dispersion 0.00 m

Calculate Dispersion From Linear Optics

Current Profile

Energy 130.0 MeV

Read Energy from Machine

Slice Analysis

Bunch Charge 250.000 pC

Read Charge from Machine

Time Calibration 0 psps

No Time Calibration

Smooth Image

Use Last Calibration

Fix Aspect Ratio

Subtract background

Smooth Image

Auto Gain Control

Pause

Threshold 0.050

Read Rate 1Hz

Display

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%

Screen

TDS

Fast Kickers

Machine State

Laser Heater Shutter OPEN

IBFB LFF ON

Camera Server CPU Load 84.6%


Screen

TDS

Fast Kickers

<

Measurements



- Open subtools:
 - Time Calibrator
 - Current Profiler
 - Slice Analyser
- Logbook writer
- Accumulate background (used for background subtraction in main display)
 - Also written to logbook if logbook writer used