






LUDWIG-
MAXIMILIANS-
UNIVERSITÄT
MÜNCHEN

Application of Machine Learning to the Identification of Dark Matter Haloes


Soumadeep Maiti

Carlos Correa, Alejandro Pérez Fernández, Ariel Sánchez
MPE, OPINAS




Quantum Universe Attract.Workshop, 2025

N-body simulations



- As time progresses (redshift z decreases), structures collapse, and the **cosmic web** becomes more defined
- Theoretical frameworks are difficult to model at highly **non-linear scales**
- Theoretical approach: simulation-based inference (**SBI**)


N-body simulations



- As time progresses (redshift z decreases), structures collapse, and the **cosmic web** becomes more defined
- Theoretical frameworks are difficult to model at highly **non-linear scales**
- Theoretical approach: simulation-based inference (**SBI**)
- **Dark matter haloes** appears at the highest peaks in the full density field


Why do we need a faster halo identification method?

- Current Halo Finders: **FOF** (Friends-of-Friends, Davis et al. 1985), **ROCKSTAR** (Robust Overdensity Calculation using K-Space Topologically Adaptive Refinement, Behroozi et al. 2013), etc.
- Increasing demand for **fast** and **mass** production of halo catalogue without sacrificing accuracy
- Halo identification in bigger simulations are computationally expensive




Why do we need a faster halo identification method?

- Current Halo Finders: **FOF** (Friends-of-Friends, Davis et al. 1985), **ROCKSTAR** (Robust Overdensity Calculation using K-Space Topologically Adaptive Refinement, Behroozi et al. 2013), etc.
- Increasing demand for **fast** and **mass** production of halo catalogue without sacrificing accuracy
- Halo identification in bigger simulations are computationally expensive




Why do we need a faster halo identification method?

- Current Halo Finders: **FOF** (Friends-of-Friends, Davis et al. 1985), **ROCKSTAR** (Robust Overdensity Calculation using K-Space Topologically Adaptive Refinement, Behroozi et al. 2013), etc.
- Increasing demand for **fast and mass** production of halo catalogue without sacrificing accuracy
- Halo identification in bigger simulations are computationally expensive



Convolutional Neural Networks


An example: Image segmentation (V-Net)



- State-of-the-art architecture
- Applications: Medical imaging, video surveillance, pedestrian detection, ...


Convolutional Neural Networks

An example: Image segmentation (V-Net)




- State-of-the-art architecture
- Applications: Medical imaging, video surveillance, pedestrian detection, ...


Learning the Dark Matter Particles




Learning the Dark Matter Particles




Learning the Dark Matter Particles



Learning the Dark Matter Particles



Learning the Dark Matter Particles



Building Dataset


- Cosmology: Planck cosmology
- Simulation: **Set ref** using Gadget4 (Springel et al. 2021)
- Apply **Rockstar** on the Snapshots
- Label DM particles (**1, 0**) based on the Halo Catalogue
- 500 realisations: Input($\overrightarrow{\psi_i}, \overrightarrow{\mathbf{v_i}}$)

Building Dataset

- Cosmology: Planck cosmology
- Simulation: **Set ref** using Gadget4 (Springel et al. 2021)
- Apply **Rockstar** on the Snapshots
- Label DM particles (**1, 0**) based on the Halo Catalogue
- 500 realisations: Input($\overrightarrow{\psi_i}, \overrightarrow{v_i}$)
 - Training: 350
 - Validation: 50
 - Testing: 100


Building Dataset

- Cosmology: Planck cosmology
- Simulation: **Set ref** using Gadget4 (Springel et al. 2021)
- Apply **Rockstar** on the Snapshots
- Label DM particles (**1, 0**) based on the Halo Catalogue
- 500 realisations: Input($\overrightarrow{\psi_i}, \overrightarrow{v_i}$)
 - Training: 350
 - Validation: 50
 - Testing: 100




CNNs' Performance

CNNs' Performance



CNNs' Performance


Confusion Matrix




- Correctly Classified: **98.69%**
- Misclassified: **1.31%**

CNNs' Performance

Confusion Matrix




Model Performance



- Correctly Classified: **98.69%**
- Misclassified: **1.31%**

Trained Models

ROCKSTAR



Resolution Increase ↓ Mass Resolution	M_{200b}	M_{vir}
$L200 - N64^3$	✓	✓
$L400 - N128^3$	✓	✓
$L200 - N128^3$	✓	✓
$L100 - N128^3$	✓	✓

Trained Model on RAVEN GPUs (MPCDF)

Trained Models

ROCKSTAR


Resolution Increase
↓

Mass Resolution	M_{200b}	M_{vir}
$L200 - N64^3$	✓	✓
$L400 - N128^3$	✓	✓
$L200 - N128^3$	✓	✓
$L100 - N128^3$	✓	✓


Trained Model on RAVEN GPUs (MPCDF)

Emulator Output


Emulator Output



Emulator Output



Emulator Output



Recovering Centres of Emulator Output

- Applied FoF on Emulator Identified Positive (TP+FP) Particles
- One-to-one correspondence of Rockstar and FoF Centers.

Recovering Centres of Emulator Output

- Applied FoF on Emulator Identified Positive (TP+FP) Particles
- One-to-one correspondence of Rockstar and FoF Centers.


$$\hookrightarrow d_{FR} = \begin{cases} \leq R_{200b}, & \text{Matched Haloes} \\ > R_{200b}, & \text{Unmatched Haloes} \end{cases}$$

Recovering Centres of Emulator Output

$L200 - N128^3$


- Applied FoF on Emulator Identified Positive (TP+FP) Particles
- One-to-one correspondence of Rockstar and FoF Centers.

$$\hookrightarrow d_{FR} = \begin{cases} \leq R_{200b}, & \text{Matched Haloes} \\ > R_{200b}, & \text{Unmatched Haloes} \end{cases}$$





Halo Matchings



Halo Matchings



Halo Matchings




Position and Velocity Recovery




Clustering Statistics

Clustering Statistics




Clustering Statistics


Halo Mass Function



Power Spectrum



Runtime Comparison




Conclusions

Final Remarks and Future work


- **Massive and Fast** production of **halo catalogues** for cosmological analyses
- Halo Finder based on ML 2 steps: **classification** of particles with a CNN and **clustering algorithm** (FoF) to get the centers
- Our models:
 - **Resolutions:** $L200 - N128^3$, $L100 - N128^3$, etc.
 - **Mass definitions:** M_{200b} , M_{vir}
- **Classification step** works at **particle level** and it is cost-effective. Metrics show a very good performance (99% in accuracy)
- **Centre recovery step** is also working very well, as the matching analysis shows
- However it is still a bottleneck because of using FoF (work in progress $\longrightarrow$ extension of the CNN to also do this task)
- Apply our method to **bigger box** sizes. With the model of $L100 - N128^3$ we can work on $L1500 - N2048^3$ (work in progress)
- Cosmological analysis (work in progress)

Thank You

Backup



M_{vir}



M_{FoF}

