

Status of the Detector Development Program WP-75

Markus Kuster, Jolanta Sztuk-Dambietz, Patrick Gessler, Andreas Koch,

Monica Turcato

May, 14 2012 11th Meeting of the European XFEL Detector Advisory Committee European XFEL GmbH, Hamburg

European XFEL Detectors



AGIPD Adaptive Gain Integrating Pixel Detector (AGIPD)



Energy range 3 - 13 keV Dynamic range 10⁴@12 keV Single Photon Sens.×yGap Storage Cells ≈ 300

DEPFET Sensor with Signal Compression (DSSC)

Energy range 0.5 - 6 keV (25 keV) Dynamic range 6000 ph/pix/pulse@1 keV Single Photon Sens. Regulator Board Storage Cells ≈ 640

Large Pixel Detector (LPD)



Energy range 5 (1) - 20 keV (25 keV) Dynamic range 10⁵@12 keV Single Photon Sens. Storage Cells ≈ 512

Other Detectors

- APDs, SDDs, strip detectors for high repetition rate applications (e.g. veto, dispersive spectrometers)
- Small area, low rep. rate, low energy 2D imaging detectors

XFEL WP-75 Base Line



2D Imaging Detectors

Baseline

1 Mpix 2x DSSC, 2x AGIPD, and 1x LPD

Potential non-baseline contribution:

SFX user consortia 4Mpix AGIPD

Particle Detectors

No specific request from leading scientists up to now.

1D/2D Small Area Detectors Low rep. Rate/Low E Detectors

- CCDs for day one low speed/E
- Strip detectors for spectroscopy
- SDDs and APDs for calibration, veto etc.

High Energy Detectors for E > 20 keV

Requirement definition

General Infrastructure

- Test and calibration environment
- Laboratories + equipment

XFEL People Joining WP-75

- Detector Scientists
 - Jolanta Sztuk-Dambietz since 4. October 2011
 - Interfacing to AGIPD
 - Detector calibration working group
 - Monica Turcato since 1. March 2012
 - Interfacing to DSSC
 - Radiation damage studies with Uni HH/DESY
 - Small area 2D detectors and strip detectors
- Software Engineer/Physicist
 - Steffen Hauf starting 1. September 2012
 - Calibration, analysis and image processing software
 - Calibration data base
 - Detector performance and response simulation







European

XFEL WP-75 Group Structure





May, 14 2012

11th Meeting of the European XFEL DAC

XFEL WP-75 Status

- Implementation phase
 - Negotiations on extension of contracts with LPD and DSSC are ongoing
 - Definition of deliverables and milestones
- Radiation damage
 - Negotiations with Uni Hamburg and HASYLAB
 - Activities continued with Uni Hamburg E. Garutti/R. Klanner
 - Device simulation and optimization
 - Radiation damage tests
 - Contribution from XFEL 0.2 FTE (M. Turcato)

Maintain expertise in Hamburg area!



XFEL WP-75 Status



- Definition of calibration infrastructure requirements
 - requirement document Q3/2012
- Operation phase and life cycle management of imaging detectors
 - Spare parts for imaging detectors
 - Requirements for sensors tiles, cooling etc
 - Negotiation with consortia: delivery, time scale ...
 - Definition of the transition from start-up to operation phase
 - Analysis software, performance simulation etc.
 - Start activities at XFEL Q3/2012
 - Definition of software requirements, implementation
- Calibration working group
 - 2nd meeting on March, 7th 2012
 - Detailed summary will be presented by J. Sztuk-Dambietz



XFEL WP-75 Status



- Detectors for spectroscopy, veto and low repetition rate applications
 - APDs, SDD, CCDs, strip detectors ...
 - Evaluating different options for day one
 - Defining requirements beyond day one

XFEL XFEL ↔ Link Detector Consortia

- Interface to LPD Andreas Koch
 - Monthly integration meetings + weekly teleconferences
 - Consortia members + leading scientists + WP-75/76
- Interface to DSSC Monica Turcato
 - Integration meetings on request
 - Consortia members + leading scientists + WP-75/76
- Interface to AGIPD Jolanta Sztuk-Dambietz
 - Monthly integration meetings
 - Consortia members + leading scientists + WP-75/76
 - XFEL participation in regular AGIPD meetings



XFEL

Detector mechanics

d P C

Flexible hole

DSSC

Cooling

. . .

- Experiment integration
- Software integration



AGIPD



XFEL Detector Laboratory (Start Up/Operation Phase)



HERA South Hall

- Start up solution for detector, beam line optics, diagnostics etc.
- Clean tents for integration and test environments for prototype 2D detectors
- Development of calibration infrastructure
- Interim IT infrastructure, elect. lab



XFEL Headquarters (XHQ)

- Clean room for test, qualification, calibration + detector laboratories
- Detector electronics test laboratory
- Storage for detector, vacuum, electronics etc. components
- IT infrastructure



XFEL Detector Laboratory – Start Up (May 2012)

Clean + Electronics Laboratory



HERA South 6th Floor

- Definition of laboratory requirements
- Electronics laboratory
- Detector test laboratory
 - Electricity, gases ...
 - Clean tent
 - Measurement equipment
 - Laboratory equipment
 - Furniture
- Safety and risk assessment
- Calibration sources
- Installation of detector test setup



Detector Laboratory – Start Up (May 2012)



HERA South 6th Floor

- Definition of laboratory requirements
- Electronics laboratory
- Detector test laboratory
 - Electricity, gases ...
 - Clean tent
 - Measurement equipment
 - Laboratory equipment
 - Furniture
- Safety and risk assessment
- Calibration sources
- Installation of detector test setup



XFEL XHQ – XFEL Headquarters (May 2012)



Detector Laboratories

- Clean room 225 m²
 - Detectors WP-75, diagnostics WP-74, beam line optics WP-73
- Detector test laboratories 100 m²
 - Prototype system tests, R&D
- Storage space 50 m²
 - Spares, loan pool ...

Clean Room Laboratory

- Laboratory specifications and requirements
- First floor plan
- Detailed laboratory planning Q3 2012
 - Planning of functional areas
 - Furniture
 - Equipment
 - Safety aspects/risks assessment
 - EMI aspects
- Entrust external planning office
- Installation 2014/15
- Ready for usage > 2015



XFEL Small Area 2D Detectors – pnCCD Test System



- Test bed and reference test system
 - Laboratory infrastructure
 - Detector support
 - PLC control system for vacuum/DAQ system
 - Commissioning cooling/ vacuum system
 - FE electronics Q3 2012
 - DAQ integration
 Q4 2012
 - Analysis software Q4 2012
- Prototype for small and compact 2D imaging systems



European XFEL Low Rep. Rate/Low E Detector for Day One

Motivation

Labs

- Mitigate risk for 2D detectors
- Backup with reduced performance
- Day one solution for low energies/small pixels

Status

- Market scan
- Identification of low risk solutions
- First performance tests
- Preparation of MB proposal
- MoU/contract negotiations





XFEL Low E/Rep. Rate Detector - LBNL Fast CCD



- Fully depleted CCD 1920 x 960 pixels
- Energy range 0.25 < E < 6 keV</p>
- Pixel size 30 µm x 30 µm
- Read out 100 200 fps

QE

- > 80 % 1 8 keV
 - > 50 % 250 eV
- Electronic noise < 50 e⁻ rms
- Well depth

10⁶ e⁻

First performance tests OK



Infrastructure XFEL Laboratory Space First Beam Commissioning Lab Test Detector R&D/Construction Data Taking/DAQ Int.

May, 14 2012

11th Meeting of the European XFEL DAC

M. Kuster



May, 14 2012

11th Meeting of the European XFEL DAC

M. Kuster



May, 14 2012

11th Meeting of the European XFEL DAC

M. Kuster

XFEL Summary and Conclusions



- Build-up of detector group is progressing well
- Communication between XFEL and consortia has been improved
- Day one options for 2D imaging detectors technologies for low energy and low repetition rate applications have been identified)
- Installation and planning of laboratory, test and R&D infrastructure for Schenefeld and HERA South is in progress
- Integration of first small area detector system started (DAQ, control, detector ...)
- Planning commissioning and integration schedule for detectors
- Second generation 2D imaging detectors
 - Study of potential solutions has been started