




Wir schaffen Wissen - heute für morgen

Yevgeniy Ivanisenko
Mini-workshop on Longitudinal Diagnostics for FELs


Electro-Optic Experiments at PSI

- Electro-optic longitudinal bunch profile monitors at SwissFEL
- Technical scheme of EO monitor implementation
- EO system status at SITF
- EO experiments
- Summary




- Spectral decoding technique
- Phase 2 (2016)
- Experiments at SwissFEL Injector Test Facility


- Spectral decoding technique



- EO system scheme





- Oscillator of EOM1 (before compression) was moved to EOM2, EOM1 is out of operation.
- EOM2 (after compression) is running and used for tests and investigations.
The GaP crystal was exchanged.
- A new oscillator was assembled for PSI at DESY.





- Frequency time domain pairs

Spectrometer



Autocorrelator




- EOM2 oscillator was not operating properly. It was replaced by an oscillator from EOM1. Correct mode-locking: mid of September. Still there ...

14.9.2013



9.11.2013



■ Overlap signal



SO - Signal with shutter opened

SC - Signal with shutter closed

$$(SO-SC)/SC = 0.8/16.8$$


After crystal replacement

$$(SO-SC)/SC = 0.8/14.0$$




■ Laser spectrum


Oscillator intra-cavity




Oscillator output



Amplifier output



Central peak value varies
from 10k to 30k



- Two EO monitors are foreseen for SwissFEL Phase 2 (2016)
- Two complete systems were built at SITF. There is only one operational laser oscillator at PSI at the moment, a new one was recently assembled at DESY.
- EO system development is nearly finished, some additional electronics for full remote control.
- The laser stability is not sufficient for a reliable bunch longitudinal profile measurement, to be improved before the next run (early 2014).